

no.6 PU rubber-granulate surfacing system



cleaning system with treatment	object	date	
end of construction	address	customer	
	room classification	representative	

work process; select one work stage from each number

work process: select one work stage from each number									
	cleaning method	recommendations * chemical products	dosage		recommendations machine / tool	comments			
1	dry vacuum cleaning			Neverclog filter without ring Filter bag with ring	Fwinvac / Duovac / Silento /	large areas: sweeping			
2	dusting damp mopping			V Multi squeegee/	Balit Varifix/ Balit/				
	cleaning without maintenance care pro	oduct (if coating follows	s)						
3	wet mopping direct method	Ecofloor V Reshine V Antiwax forte	0.5 - 1% 3 - 5% 2 - 5%	Microsol mop/	Socar / Drewell				
3	scrubber drying direct method	Ecofloor V Antiwax forte V Reshine	0.5 - 1% 2 - 5% 3 - 5%	V Pad blue/	Duomatic / Laser Mambo / Samba Sprinter / iMatic				
3	wet scrubbing and wet vacuuming	Antiwax forte Remat	2 - 5% 1 - 5%	V Pad green/	Monomatic LS / Watertank Duovac /	heavily soiled			
	cleaning with maintenance care (first	protective treatment wit	h same pro	roduct as in maintenance cleaning)					
4	wet mopping direct method	Redur	3%	Flat mop/ Micro-Mop Top/	Socar / Drewell				
4	scrubber drying direct method	Redur	3%		Duomatic / Laser Mambo / Samba Sprinter / iMatic				
4	spray cleaning full spray	Polyspray Elfspray	100% 100%		Monomatic DS / Spray unit	after polishing			

^{*} basic treatment / structure: B: coated / C: waxed / D: oiled / E: sealed / F: untreated / G: maintenance care product / P: polishing / S: structured / V: heavily soiled

When spray cleaning, you should change your pad often important:



no.6 PU rubber-granulate surfacing system



	maintenance cleaning				object	date	
				a	ddress	customer	
work	process: select one work stage from	each nui	mber	room classif	fication	representative	
П		frequ	recommendations		recommendations	recommendations	
>	cleaning method	ency	* chemical products	dosage	* pad / brush / mop / cloth	machine / tool	comments
1	dusting damp mopping				Masslinn / Floorwit Synthetic fur V Multi squeegee/	Balit Varifix/ Balit/	
2	chewing gum removal		Karpfrost Karpotek	100%			if needed
	cleaning without maintenance						
3	wet mopping direct method		Ecofloor Reshine Alcosal	0.5 - 1% 1 - 2% 1 - 2%	Mop Microbrush/ Micro-Mop Top/ Mop Variwet	Wetbox system Socar / Drewell Variwet / B. Varifix	
3	scrubber drying direct method		Ecofloor Reshine Libero	0.5 - 1% 1 - 2% 0.5 - 3%	Pad red/	Duomatic / Laser Mambo / Samba Sprinter / iMatic	
3	polishing, vacuum polishing	[]			B Pad Blue Ice/ B Microsol fibre pad/	Monomatic HS / Suction ring Monor	after polishing
	cleaning with maintenance						
3	wet mopping direct method		Redur	1%	Mop Microbrush/ Micro-Mop Top/ Mop Variwet	Wetbox system Socar / Drewell Variwet / B. Varifix	
3	scrubber drying direct method		Redur	1%	Pad red/	Duomatic / Laser Mambo / Samba Sprinter / iMatic	
3	spray cleaning partial spray		Polyspray Elfspray	100% 100%	Pad red/ P Pad yellow/	Monomatic DS / Spray unit	after polishing
3	US spray cleaning partial spray		B US Restorer	100%	B US pad pink/ P US pad yellow/	Monomatic US / Spray unit	after polishing

important: When spray cleaning, you should change your pad often

^{*} basic treatment / structure: B: coated / C: waxed / D: oiled / E: sealed / F: untreated / G: maintenance care product / P: polishing / S: structured / V: heavily soiled

no.6 PU rubber-granulate surfacing system



	interim cleaning			а	objed ddres	· -	date customer	
work	process: select one work stage from	each nu	mber	room classif			representative	
	cleaning method	frequ ency	recommendations * chemical products	dosage	*	recommendations pad / brush / mop / cloth	recommendations machine / tool	comments
1	dusting damp mopping				V	Masslinn / Floorwit Synthetic fur Multi squeegee/	Balit Varifix/ Balit/	
1	dry vacuum cleaning	9 []			V	Dust roller nozzle	Monovac / Scuba	large areas: sweeping
2	chewing gum removal		Karpfrost Karpotek	100%				if needed
	cleaning without maintenance							
3	wet mopping indirect method		Reshine F Antiwax forte G Rewit 2000	3 - 5% 2 - 5% 2 - 5%	V	Mop Microbrush/ Micro-Mop Top/ Flat mop/	Wetbox system Socar / Drewell	
3	scrubber drying indirect method		Reshine F Antiwax forte G Rewit 2000	3 - 5% 2 - 5% 2 - 5%	V V	Pad red/ Pad blue/ Pad green/	Duomatic / Laser Mambo / Samba Sprinter / iMatic	
3	polishing, vacuum polishing				В	Pad Blue Ice/ Microsol fibre pad/	Monomatic HS / Suction ring Monor	after polishing
	cleaning with maintenance							
3	spray cleaning full spray		Polyspray Elfspray	100% 100%	Р	Pad red/ Pad yellow/	Monomatic DS / Spray unit	after polishing
3	US spray cleaning full spray		B US Restorer	100%		US pad pink/ US pad yellow/	Monomatic US / Spray unit	after polishing

important: When spray cleaning, you should change your pad often For initial cleaning after interim cleaning, see "initial cleaning".

^{*} basic treatment / structure: B: coated / C: waxed / D: oiled / E: sealed / F: untreated / G: maintenance care product / P: polishing / S: structured / V: heavily soiled

no.6 PU rubber-granulate surfacing system



	basic cleaning				objec [.] ddress		date customer		-
work	process: select one work stage from	each nui	mber	room classif	icatior	1	representative		
	cleaning method	frequ ency	recommendations * chemical products	dosage	*	recommendations pad / brush / mop / cloth	recommendations machine / tool	comments	
1	dusting damp mopping				V	Masslinn / Floorwit Synthetic fur Multi squeegee/	Balit Varifix/ Balit/		
1	dry vacuum cleaning				V	Dust roller nozzle	Monovac / Scuba		
2	chewing gum removal	[]	Karpfrost Karpotek	100%				if needed	
	cleaning without maintenance								
3	wet scrubbing and wet vacuuming		B Relino Antiwax forte	20 - 50% 2 - 5%	B G	Pad green/ Pad blue/	Monomatic I / Watertank Duovac /		
3	scrubber drying indirect method		B Relino Antiwax forte	20 - 50% 2 - 5%	B G	Pad green/ Pad blue/	Duomatic / Laser Sprinter / iMatic Mambo / Samba	2 m	
3	spray cleaning full spray	[]	B Antiwax forte	30 - 50%	В	Pad green/ Pad blue/	Monomatic I / Spray unit		
4	rinsing		pure water			Pad blue/) Microsol fibre pad/	Monomatic I / Duovac / Duomatic / Laser		pH 7

change pad often important:

Do not coat floors with PUR coating provided in the factory

Use a coin or a key to do a scratch test, to check if all the protective coating has been removed.

When white abrasion occurs, carry out a full clean to remove all the protective coating

For initial cleaning after basic cleaning, see "initial cleaning".

^{*} basic treatment / structure: B: coated / C: waxed / D: oiled / E: sealed / F: untreated / G: maintenance care product / P: polishing / S: structured / V: heavily soiled



no.6 PU rubber-granulate surfacing system



	protective treatment			object	date	
			ac	ddress	customer	
work	process: select one work stage from each nur	mber	room classif	ication	representative	
	cleaning method	recommendations * chemical products	dosage	recommendations * pad / brush / mop / cloth	recommendations machine / tool	comments
1	dusting damp mopping			Masslinn 2000/Floorwit white Synthetic fur	Balit Varifix / Balit/	
	coating					
2	coating	Mepol HM Mepol H Mepol HX	100% 100% 100%	Cover for Florfix Flat mop/	Florfix/ Drewell/ Buket plast 22l	1 - 3 thin layers
2	waxing	Polish	100%	Cover for Florfix Flat mop/	Florfix/ Drewell/ Buket plast 22l	1 - 3 thin layers
	buffing wax treatment (only if necessa	ry)				
3	dusting damp mopping			Masslinn 2000/Floorwit white Synthetic fur	Balit Varifix/ Balit/	
4	polishing, vacuum polishing			C Pad yellow/	Monomatic HS / Suction ring Monon Monomatic DS /	after polishing

important: if needed

before protective treatment: the floor must be perfectly stripped, thoroughly rinsed and completely dry!

Let dry protection treatment completely between the layers and before use

Process treatement of protection: see descriptione of method

For initial cleaning with maintenance cleaner after protective treatment, see "initial cleaning".

^{*} basic treatment / structure: B: coated / C: waxed / D: oiled / E: sealed / F: untreated / G: maintenance care product / P: polishing / S: structured / V: heavily soiled





PU rubber-granulate surfacing system



Information about the flooring



Wetrok AG cannot accept any liability for damages due to improper use.

For security information, see the safety data sheet at www.wetrok.ch.

Wear protection: gloves, safety goggles, work clothes


Follow the information and remarks on the label, product data sheet and material safety data sheet.

The product data sheet describes the product and gives information about its application, storage. See www.wetrok.ch

The recommended colours of pad and brushes consist to the actual wWetrok product range

Follow the special cleaning and care instructions of the floor manufacturer

The cleaning and care instructions are recommendations and suggestions and apply to floorings in object quality.



Rubber granulate floor coverings are sensitive to strong alkalines such as soft soap and basic cleaners. Colour change: material damage! Rubber granulate floor coverings are sensitive to certain solvents such as ketone and ester.

Fat-soluble colorants such as shoe polish or asphalt can penetrate into rubber granulate floor coverings: diffusion

Polyurethane surfaces are relatively insensitive to abrasive pads and brushes.

Polyurethane surfaces are insensitive to cigarette burns, glowing cigarettes and deposit marks.



A polyurethane rubber granulate system is a synthetic elastic covering made from rubber granulates and a binder, compacted and smoothed, with a polyurethane use-surface. Polyurethane rubber granulate systems are applied in a seamless manner.

Distinguishing feature: fire assay with a glowing hot needle in an inconspicuous place: needle does not penetrate, no acrid smell, no crater formation.



Remove loose dirt before every cleaning, damp mop smooth floors and vacuum structured floors.

Cleaning agents and surface treatments may alter the appearance and properties of a floor's surface.

Test on an inconspicuous spot to find which product is suitable for your requirements.

Test beforehand on an inconspicuous spot to see if the cleaning agent or surface treatment damages the floor.

Dirt-trapping zones, incl. dirt-trapping mats (Wetrok Gardamat) in the entrance, at least 7m long, greatly reduce the amount of dirt tracked into the building.

If you have any questions, please don't hesitate to contact us.

For training courses, contact the Wetrok Academy, tel. +41 (0)43 255 51 43 or academy@wetrok.ch.