

# General instructions for cleaning and care

## no.21 Asphalt (smooth)























**cleaning system without treatment  
end of construction**

object \_\_\_\_\_  
address \_\_\_\_\_  
room classification \_\_\_\_\_

date \_\_\_\_\_  
customer \_\_\_\_\_  
representative \_\_\_\_\_

work process: select one work stage from each number

	cleaning method	* recommendations chemical products	dosage	* recommendations pad / brush / mop / cloth	recommendations machine / tool	comments
1	 dry vacuum cleaning			<b>Dust roller nozzle</b> <b>Neverclog filter without ring</b> <b>Filter bag with ring</b>	<b>Twinvac /</b> Duovac / Silento /	
1	 vacuum sweeping sweeping				<b>Speedmatic Twister</b> Turbo Sweep	large areas: <div>2 m</div>
2	 dusting damp mopping			V <b>Masslinn 2000/Floorwit white</b> Multi squeegee/	<b>Balit Varifix/</b> Balit/	
cleaning without maintenance care product (if coating follows)						
3	 wet mopping direct method	<b>Ecofloor</b> Polex V Rewit 2000	<b>0.5 - 1%</b> 2 - 4% 2 - 5%	<b>Micro-Mop Top/</b> Microsol mop/	<b>Socar / Drewell</b>	
3	 scrubber drying direct method	<b>Ecofloor</b> Polex V Rewit 2000	<b>0.5 - 1%</b> 2 - 4% 2 - 5%	 <b>Microsol fibre pad/</b>  Pad red/	<b>Duomatic / Laser</b> Mambo / Samba Sprinter / iMatic	
3	 wet scrubbing and wet vacuuming	<b>Polex</b> V Rewit 2000	<b>2 - 4%</b> 2 - 5%	 <b>Microsol fibre pad/</b>  Pad red/ V  Pad blue/	<b>Monomatic I /</b> <b>Watertank</b> <b>Duovac /</b>	heavily soiled  
4	 stain removal	See cleaning instruction no 41				if needed
cleaning with maintenance care (first protective treatment with same product as in maintenance cleaning)						
5	 wet mopping direct method	<b>Redur</b> F Brill	<b>3%</b> 3 - 5%	<b>Flat mop/</b> Micro-Mop Top/	<b>Socar / Drewell</b>	Brill should be used with flat mop only
5	 scrubber drying direct method	<b>Redur</b> F Brill	<b>3%</b> 3 - 5%	 <b>Microsol fibre pad/</b>  Pad red/	<b>Duomatic /</b> Mambo / Samba Sprinter / iMatic	

\* basic treatment / structure: B: coated / C: waxed / D: oiled / E: sealed / F: untreated / G: maintenance care product / P: polishing / S: structured / V: heavily soiled

# General instructions for cleaning and care

## no.21 Asphalt (smooth)



### maintenance cleaning

object \_\_\_\_\_

date \_\_\_\_\_

















address \_\_\_\_\_

customer \_\_\_\_\_

work process: select one work stage from each number

room classification \_\_\_\_\_

representative \_\_\_\_\_

	cleaning method	frequency	* recommendations chemical products	dosage	* recommendations pad / brush / mop / cloth	recommendations machine / tool	comments
1	 dusting damp mopping	<input type="checkbox"/>			B <b>Masslinn 2000/Floorwit white</b> B Synthetic fur	<b>Balit Varifix/</b> Balit/	
1	 dry vacuum cleaning	<input type="checkbox"/>			F <b>Dust roller nozzle</b> V Dust roller nozzle	<b>Monovac /</b> Scuba	
1	 vacuum sweeping sweeping	<input type="checkbox"/>				<b>Speedmatic Twister</b> Turbo Sweep	large areas: 
2	 chewing gum removal	<input type="checkbox"/>	<b>Karpfrost</b> Karpotek	<b>100%</b>		<b>Monovac /</b>	if needed 
<b>cleaning without maintenance</b>							
3	 wet mopping direct method	<input type="checkbox"/>	<b>Ecofloor</b> Polex Biosan	<b>0.5 - 1%</b> 0.5 - 1% 0.8 - 1.5%	<b>Mop Microbrush/</b> Micro-Mop Top/ Mop Variwet	<b>Wetbox system</b> Socar / Drewell Variwet / B. Varifix	
3	 scrubber drying direct method	<input type="checkbox"/>	<b>Ecofloor</b> Polex	<b>0.5 - 1%</b> 0.5 - 1%	 <b>Microsol fibre pad/</b> B  Pad red/	<b>Duomatic / Laser</b> Mambo / Samba Sprinter / iMatic	
<b>cleaning with maintenance</b>							
3	 wet mopping direct method	<input type="checkbox"/>	<b>Redur</b>	<b>1%</b>	<b>Mop Microbrush/</b> Micro-Mop Top/ Mop Variwet	<b>Wetbox system</b> Socar / Drewell Variwet / B. Varifix	
3	 scrubber drying direct method	<input type="checkbox"/>	<b>Redur</b> F Brill	<b>1%</b> 1 - 2%	 <b>Microsol fibre pad/</b> B  Pad red/	<b>Duomatic / Laser</b> Mambo / Samba Sprinter / iMatic	

\* basic treatment / structure: B: coated / C: waxed / D: oiled / E: sealed / F: untreated / G: maintenance care product / P: polishing / S: structured / V: heavily soiled

# General instructions for cleaning and care

no.21  Asphalt (smooth)



## interim cleaning

object \_\_\_\_\_

date \_\_\_\_\_















address \_\_\_\_\_

customer \_\_\_\_\_

work process: select one work stage from each number

room classification \_\_\_\_\_

representative \_\_\_\_\_

	cleaning method	frequency	* recommendations chemical products	dosage	* recommendations pad / brush / mop / cloth	recommendations machine / tool	comments
1	 dusting damp mopping	<input type="checkbox"/>			B <b>Masslinn 2000/Floorwit white</b> B Synthetic fur	<b>Balit Varifix/</b> Balit/	
1	 dry vacuum cleaning	<input type="checkbox"/>			F <b>Dust roller nozzle</b> S Dust roller nozzle	<b>Monovac /</b> Scuba	
1	 vacuum sweeping sweeping	<input type="checkbox"/>				<b>Speedmatic Twister</b> Turbo Sweep	large areas: <input type="checkbox"/> 2 m
2	 chewing gum removal	<input type="checkbox"/>	<b>Karpfrost</b> Karpotek	100%			if needed <input type="checkbox"/>
<b>cleaning without maintenance</b>							
3	 wet mopping indirect method	<input type="checkbox"/>	<b>Polex</b> G Rewit 2000	2 - 4% 2 - 5%	<b>Mop Microbrush/</b> Micro-Mop Top/	<b>Wetbox system</b> Socar / Drewell	 
3	 scrubber drying indirect method	<input type="checkbox"/>	<b>Polex</b> G Rewit 2000	2 - 4% 2 - 5%	 <b>Microsol fibre pad/</b> B  Pad blue/	<b>Duomatic / Laser</b> Mambo / Samba Sprinter / iMatic	 
4	 wet mopping direct method	<input type="checkbox"/>	<b>Biosan</b>	3%	<b>Micro-Mop Top/</b> Mop Microbrush/ Mop Variwet	<b>Socar / Drewell</b> Wetbox system Variwet / B. Varifix	if needed, bad smell could be removed with 

\* basic treatment / structure: B: coated / C: waxed / D: oiled / E: sealed / F: untreated / G: maintenance care product / P: polishing / S: structured / V: heavily soiled

**important:** For initial cleaning after interim cleaning, see "initial cleaning".

# General instructions for cleaning and care

no.21  Asphalt (smooth)



## basic cleaning

object \_\_\_\_\_

date \_\_\_\_\_






















address \_\_\_\_\_

customer \_\_\_\_\_

work process: select one work stage from each number

room classification \_\_\_\_\_

representative \_\_\_\_\_

	cleaning method	frequency	* recommendations chemical products	dosage	* recommendations pad / brush / mop / cloth	recommendations machine / tool	comments
1	 dusting damp mopping	<input type="checkbox"/>			B B <b>Masslinn / Floorwit</b> Synthetic fur	<b>Balit Varifix/</b> Balit/	
1	 dry vacuum cleaning	<input type="checkbox"/>			F F <b>Dust roller nozzle</b>	<b>Monovac /</b> Scuba	
2	 chewing gum removal	<input type="checkbox"/>	<b>Karpfrost</b> Karpotek	<b>100%</b>			if needed 
<b>cleaning without maintenance</b>							
3	 wet scrubbing and wet vacuuming	<input type="checkbox"/>	<b>Rewit 2000</b>	<b>10 - 20%</b>	B ● Pad blue/ ● Pad green/	<b>Monomatic I /</b> <b>Watertank</b> <b>Duovac /</b>	attention: modification of surface   
3	 scrubber drying indirect method	<input type="checkbox"/>	<b>Rewit 2000</b>	<b>10 - 20%</b>	B ● Pad blue/ ● Pad green/	<b>Duomatic / Laser</b> Mambo / Samba Sprinter / iMatic	   
4	rinsing   	<input type="checkbox"/>	<b>pure water</b>		● Pad blue/ ● Microsol fibre pad/	<b>Monomatic I /</b> <b>Duovac /</b> Duomatic / Laser	 
5	 wet mopping direct method	<input type="checkbox"/>	<b>Biosan</b>	<b>3%</b>	<b>Micro-Mop Top/</b> Mop Microbrush/ Mop Variwet	<b>Socar / Drewell</b> Wetbox system Variwet / B. Varifix	if needed, bad smell could be removed with  

\* basic treatment / structure: B: coated / C: waxed / D: oiled / E: sealed / F: untreated / G: maintenance care product / P: polishing / S: structured / V: heavily soiled

## important:

change pad often  
green and black pad on hard stone only  
Use a coin or a key to do a scratch test, to check if all the protective coating has been removed.  
When white abrasion occurs, carry out a full clean to remove all the protective coating  
For initial cleaning after basic cleaning, see "initial cleaning".

# General instructions for cleaning and care

no.21  Asphalt (smooth)



## protective treatment

object \_\_\_\_\_

date \_\_\_\_\_













address \_\_\_\_\_

customer \_\_\_\_\_

work process: select one work stage from each number

room classification \_\_\_\_\_

representative \_\_\_\_\_

		cleaning method	* recommendations chemical products	dosage	* recommendations pad / brush / mop / cloth	recommendations machine / tool	comments
1		dusting damp mopping			B <b>Masslinn 2000/Floorwit white</b> B Synthetic fur	<b>Balit Varifix/</b> Balit/	
1		dry vacuum cleaning			F <b>Dust roller nozzle</b> S Dust roller nozzle	<b>Monovac /</b> Scuba	
pore filling (only if necessary)							
2		pore filling	F <b>Porosol</b>	100%	<b>Cover for Florfix</b> Flat mop/	<b>Florfix/</b> Drewell/ Multi squeegee/	If necessary, one layer on porous surface  
coating							
3		coating	<b>Stoner</b>	100%	<b>Cover for Florfix</b> Flat mop/	<b>Florfix/</b> Drewell/ Buket plast 22l	1 - 3 thin layers  
coating							
2		impregnation	F <b>Imprasol</b>	100%	<b>Cover for Florfix</b> Flat mop/	<b>Florfix/</b> Drewell/ Buket plast 22l	apply first layer with care  

\* basic treatment / structure: B: coated / C: waxed / D: oiled / E: sealed / F: untreated / G: maintenance care product / P: polishing / S: structured / V: heavily soiled

### important:

if needed

before protective treatment: the floor must be perfectly stripped, thoroughly rinsed and completely dry!

Let dry protection treatment completely between the layers and before use

do not coat impregnated floors

Process treatment of protection: see descriptions of method

For initial cleaning with maintenance cleaner after protective treatment, see "initial cleaning".

# General instructions for cleaning and care


## no. 21 Asphalt (smooth)



### Information about the flooring



Wetrok AG cannot accept any liability for damages due to improper use.  
For security information, see the safety data sheet at [www.wetrok.ch](http://www.wetrok.ch).  
Wear protection: gloves, safety goggles, work clothes  
Follow the information and remarks on the label, product data sheet and material safety data sheet.  
The product data sheet describes the product and gives information about its application, storage. See [www.wetrok.ch](http://www.wetrok.ch)  
The recommended colours of pad and brushes consist to the actual wWetrok product range  
Follow the special cleaning and care instructions of the floor manufacturer  
The cleaning and care instructions are recommendations and suggestions and apply to floorings in object quality.



**Asphalt is sensitive to solvents, oils and fats. Do not use solvent-based cleaners or waxes!**  
**Asphalt coverings with mineral aggregates are acid-sensitive.**

Asphalt coverings are relatively insensitive to abrasive pads and brushes.  
Asphalt is temperature-sensitive and softens at temperatures above 60 °C.  
Asphalt is sensitive to high pressure loads.



Asphalt is a blend of bitumen and minerals, such as chippings, sand and stone flour.  
Mastic asphalt is cast without joints, layer thickness 15 - 30mm.  
Compressed asphalt sheets are sheets compressed under high pressure and they often have acid-sensitive cement mortar.

Distinguishing feature: solution assay: apply a little solvent (e.g. alcohol) to the asphalt covering and wipe. Dark, porous stain: material damage!



Remove loose dirt before every cleaning, damp mop smooth floors and vacuum structured floors.  
Cleaning agents and surface treatments may alter the appearance and properties of a floor's surface.  
Test on an inconspicuous spot to find which product is suitable for your requirements.  
Test beforehand on an inconspicuous spot to see if the cleaning agent or surface treatment damages the floor.  
Dirt-trapping zones, incl. dirt-trapping mats (Wetrok Gardamat) in the entrance, at least 7m long, greatly reduce the amount of dirt tracked into the building.

If you have any questions, please don't hesitate to contact us.  
For training courses, contact the Wetrok Academy, tel. +41 (0)43 255 51 43 or [academy@wetrok.ch](mailto:academy@wetrok.ch).