# no.22 Hard concrete, untreated (smooth)



#### cleaning system with treatment end of construction

 date _	object
 customer	address
representative	room classification

work process: select one work stage from each number

	process. select one work stage from each nu					
	cleaning method	recommendations * chemical products	dosage	recommendations  * pad / brush / mop / cloth	recommendations machine / tool	comments
1	dry vacuum cleaning		accugo	Dust roller nozzle Neverclog filter without ring Filter bag with ring	Twinvac / Duovac / Silento /	
1	vacuum sweeping sweeping				Speedmatic Twister Turbo Sweep	large areas: 2 m
2	dusting damp mopping			Masslinn 2000/Floorwit white	Balit Varifix/ Balit/	
	cleaning without maintenance care pr	oduct (if coating follows	s)			
3	wet mopping direct method	Ecofloor V Reshine V Antiwax forte	<b>0.5 - 1%</b> 3 - 5% 2 - 5%	<b>Micro-Mop Top</b> / Microsol mop/	Socar / Drewell	
3	scrubber drying direct method	V Reshine V Antiwax forte	<b>0.5 - 1%</b> 3 - 5% 2 - 5%	Microsol fibre pad/ Pad red/ S O Scrubbing brush PP/	Duomatic / Laser Mambo / Samba Sprinter / iMatic	
3	wet scrubbing and wet vacuuming	Antiwax forte Rewit 2000	<b>2 - 5%</b> 2 - 5%	Microsol fibre pad/ Pad red/ S O Scrubbing brush washbeton/	Monomatic LS / Duovac /	heavily soiled
3	dry sanding			V Pad green/ V Pad black/	Monomatic I / Suction ring Monor	attention: modification of surface
	cleaning with maintenance care (first	protective treatment wit	h same pro	duct as in maintenance cleaning)		
4	wet mopping direct method	Redur F Brill 2care	<b>3%</b> 3 - 5% 3 - 5%	Flat mop/ Micro-Mop Top/	Socar / Drewell	Brill should be used with flat mop only
4	scrubber drying direct method	Redur F Brill 2care	<b>3%</b> 3 - 5% 3 - 5%	Microsol fibre pad/ Pad red/ S O Scrubbing brush PP/	Duomatic / Laser Mambo / Samba Sprinter / iMatic	

<sup>\*</sup> basic treatment / structure: B: coated / C: waxed / D: oiled / E: sealed / F: untreated / G: maintenance care product / P: polishing / S: structured / V: heavily soiled



# no. 22 Hard concrete, untreated (smooth)



maintenance cleaning				object ddress		date customer			
w <u>or</u> k	process: select one work stage from	each nui	mber	room classif			representative		
	cleaning method	frequ ency	recommendations * chemical products	dosage	*	recommendations pad / brush / mop / cloth	recommendations machine / tool	comments	
1	dusting damp mopping	[]			В	Masslinn 2000/Floorwit white Synthetic fur	Balit Varifix/ Balit/		
1	dry vacuum cleaning				F S	<b>Dust roller nozzle</b> Dust roller nozzle	Monovac / Scuba		
1	vacuum sweeping sweeping						Speedmatic Twister Turbo Sweep	large areas: sweeping m	
2	chewing gum removal		<b>Karpfrost</b> Karpotek	100%				if needed	
	cleaning without maintenance								
3	wet mopping direct method		<b>Ecofloor</b> Reshine Biosan	<b>0.5 - 1%</b> 1 - 2% 0.8 - 1.5%		Micro-Mop Top/ Mop Microbrush/ Mop Variwet	Wetbox system Socar / Drewell Variwet / B. Varifix		
3	scrubber drying direct method		Ecofloor Reshine Libero	<b>0.5 - 1%</b> 1 - 2% 0.5 - 3%	W■© BS	Pad red/	<b>Duomatic</b> / <b>Laser</b> Mambo / Samba Sprinter / iMatic		
	cleaning with maintenance								
3	wet mopping direct method		<b>Redur</b> F Brill	<b>1%</b> 1 - 2%		Micro-Mop Top/ Mop Variwet Flat mop/	Wetbox system Socar / Drewell Variwet / B. Varifix	Brill should be used with flat mop only	
3	scrubber drying direct method		Redur F Brill B 2care		B (O	Microsol fibre pad/ Pad red/ Scrubbing brush PP/	Duomatic / Laser Mambo / Samba Sprinter / iMatic		

<sup>\*</sup> basic treatment / structure: B: coated / C: waxed / D: oiled / E: sealed / F: untreated / G: maintenance care product / P: polishing / S: structured / V: heavily soiled



# no.22 Hard concrete, untreated (smooth)



interim cleaning					object ddress		date customer	
	process: select one work stage from e	each nur	mber	room classifi	ication	1	representative	
	cleaning method	frequ ency	recommendations * chemical products	dosage	*	recommendations pad / brush / mop / cloth	recommendations machine / tool	comments
1	dusting damp mopping				В		Balit Varifix/ Balit/	
1	dry vacuum cleaning				FS	<b>Dust roller nozzle</b> Dust roller nozzle	Monovac / Scuba	
1	vacuum sweeping sweeping						Speedmatic Twister Turbo Sweep	large areas: 2 m
2	chewing gum removal		<b>Karpfrost</b> Karpotek	100%				if needed
	cleaning without maintenance							
3	wet mopping indirect method		Reshine G Antiwax forte	<b>3 - 5%</b> 2 - 5%		Micro-Mop Top/ Mop Microbrush/	Wetbox system Socar / Drewell	
3	scrubber drying indirect method		Reshine G Antiwax forte	<b>3 - 5%</b> 2 - 5%	B O	Microsol fibre pad/ Pad red/ Scrubbing brush PP/	Duomatic / Laser Mambo / Samba Sprinter / iMatic	
4	wet mopping direct method		Biosan	3%		Micro-Mop Top/ Mop Microbrush/ Mop Variwet	Socar / Drewell Wetbox system Variwet / B. Varifix	if needed, bad smell could be removed with

For initial cleaning after interim cleaning, see "initial cleaning". comments

<sup>\*</sup> basic treatment / structure: B: coated / C: waxed / D: oiled / E: sealed / F: untreated / G: maintenance care product / P: polishing / S: structured / V: heavily soiled



# no.22 Hard concrete, untreated (smooth)



	basic cleaning				objec	t	date		
				a	ddress	6	customer		
work	process: select one work stage from	each nui	mber	room classif	cation	1	representative		
	7	frequ	recommendations			recommendations	recommendations		
$\searrow$	cleaning method	ency	* chemical products	dosage	*	pad / brush / mop / cloth	machine / tool	comments	
1	dusting damp manning	[]			В	Masslinn 2000/Floorwit white Synthetic fur	Balit Varifix/ Balit/		
	damp mopping	1;							
					F	Dust roller nozzle	Monovac /		
1	dry vacuum cleaning				S	Dust roller nozzle	Scuba		
2	chewing gum removal		<b>Karpfrost</b> Karpotek	100%				if needed	
	cleaning without maintenance								
3	wet scrubbing and wet vacuuming		B Remat forte G Rewit 2000 Antiwax forte	<b>10 - 20%</b> 10 - 20% 30 - 50%	V	Microsol fibre pad/ Pad green/ Pad black/	Monomatic I / Watertank Duovac /	attention: modification of surface	
3	scrubber drying indirect method		B Remat forte G Rewit 2000 Antiwax forte	<b>10 - 20%</b> 10 - 20% 30 - 50%	V	Microsol fibre pad/ Pad green/ Pad black/	Duomatic / Laser Mambo / Samba Sprinter / iMatic	attention: modification of surface	
3	dry sanding	[ [ ]			٧	Pad green/ Pad black/	Monomatic I / Suction ring Monon	attention: modification of surface	
4	rinsing		pure water			Microsol fibre pad/ Pad green/	Monomatic I / Duovac / Duomatic / Laser		pH 7
5	wet mopping direct method		Biosan	3%		Micro-Mop Top/ Mop Microbrush/ Mop Variwet	Socar / Drewell Wetbox system Variwet / B. Varifix	if needed, bad smell could be removed with	

comments change pad often

green and black pad on hard stone only

Use a coin or a key to do a scratch test, to check if all the protective coating has been removed.

<sup>\*</sup> basic treatment / structure: B: coated / C: waxed / D: oiled / E: sealed / F: untreated / G: maintenance care product / P: polishing / S: structured / V: heavily soiled



### no.22 Hard concrete, untreated (smooth)



protective treatment			object			date		_	
			ac	ddress		customer			
work	process: select one work stage from each nur	mber	room classifi	cation		representative			
	cleaning method	recommendations * chemical products	dosage	*	recommendations pad / brush / mop / cloth	recommendations machine / tool	comments		
1	dusting damp mopping				Masslinn 2000/Floorwit white Synthetic fur	Balit Varifix/ Balit/			
1	dry vacuum cleaning			F V	<b>Dust roller nozzle</b> Dust roller nozzle	<b>Duovac</b> / Scuba			
	pore filling (only if necessary)								
2	pore filling	Porosol	100%		Cover for Florfix Flat mop/	Florfix/ Drewell/ Multi squeegee/	If necessary, one layer on porous surface		
	coating								
3	coating	Stoner	100%		Cover for Florfix Flat mop/	Florfix/ Drewell/ Buket plast 22l	1 - 3 thin layers		
	coating								
2	impregnation	F Imprasol	100%		Cover for Florfix Flat mop/	Florfix/ Drewell/ Buket plast 22l	apply first layer with care		

before protective treatment: the floor must be perfectly stripped, thoroughly rinsed and completely dry! comments

pore filling on heavy used floors only

Let dry protection treatment completely between the layers and before use

do not coat impregnated floors

Process treatement of protection: see descriptione of method

For initial cleaning with maintenance cleaner after protective treatment, see "initial cleaning".

<sup>\*</sup> basic treatment / structure: B: coated / C: waxed / D: oiled / E: sealed / F: untreated / G: maintenance care product / P: polishing / S: structured / V: heavily soiled





### no.22 Hard concrete, untreated (smooth)



#### Information about the flooring



Wetrok AG cannot accept any liability for damages due to improper use.

For security information, see the safety data sheet at www.wetrok.ch.

Wear protection: gloves, safety goggles, work clothes

Follow the information and remarks on the label, product data sheet and material safety data sheet.

The product data sheet describes the product and gives information about its application, storage. See www.wetrok.ch

The recommended colours of pad and brushes consist to the actual wWetrok product range

Follow the special cleaning and care instructions of the floor manufacturer

The cleaning and care instructions are recommendations and suggestions and apply to floorings in object quality.



#### Strong acids can destroy hard concrete!

The fine surface material (laitance) can be removed mechanically. This changes the surface and the appearance of the covering.

Hard concrete coverings are relatively insensitive to abrasive pads and brushes.

Hard concrete coverings are largely insensitive to alkalines, fats, oils and solvents: staining!



Hard concrete is a 100% natural product consisting of cement mortar and fillers such as gravel for concrete, basalt, granite, quartz and carborundum.

Distinguishing feature: acid assay: apply a little sanitary cleaner to the hard concrete covering. Immediately foams up: material damage!



Remove loose dirt before every cleaning, damp mop smooth floors and vacuum structured floors.

Cleaning agents and surface treatments may alter the appearance and properties of a floor's surface.

Test on an inconspicuous spot to find which product is suitable for your requirements.

Test beforehand on an inconspicuous spot to see if the cleaning agent or surface treatment damages the floor.

Dirt-trapping zones, incl. dirt-trapping mats (Wetrok Gardamat) in the entrance, at least 7m long, greatly reduce the amount of dirt tracked into the building.

If you have any questions, please don't hesitate to contact us.

For training courses, contact the Wetrok Academy, tel. +41 (0)43 255 51 43 or academy@wetrok.ch.

Wetrok AG Steinackerstrasse 62, CH-8302 Kloten, Tel +41 (0)43 255 51 51, info@wetrok.ch, www.wetrok.ch, www.wetrok.com