no.27 Synthetic stone, polished, paving stones and Terrazzo



cleaning system with treatment	object_	date _	
end of construction	address	customer	
	room classification	representative	

work	work process: select one work stage from each number									
	cleaning method	recommendations * chemical products	dosage	* pac	d / brush / mop / cloth	recommendations machine / tool	comments			
1	dry vacuum cleaning			Nev Filt	verclog filter without ring ter bag with ring	Twinvac / Duovac / Silento /	large areas: sweeping			
2	dusting damp mopping			_	sslinn 2000/Floorwit white Iti squeegee/	Balit Varifix/ Balit/				
	cleaning without maintenance care pro									
3	wet mopping direct method	Ecofloor V Reshine V Antiwax forte	0.5 - 1% 3 - 5% 2 - 5%		cro-Mop Top/ crosol mop/	Socar / Drewell				
3	scrubber drying direct method	Ecofloor V Reshine V Antiwax forte	0.5 - 1% 3 - 5% 2 - 5%	V Pac	d blue/ d green/		green and black pad on hard stone only			
3	wet scrubbing and wet vacuuming	Reshine Antiwax forte	3 - 5% 2 - 5%	Pac	d blue/	Monomatic LS / Watertank Duovac /	heavily soiled			
4	stain removal	See cleaning instructi					if needed			
	cleaning with maintenance care (first						-			
5	wet mopping direct method	Redur F Brill	3% 3 - 5%		cro-Mop Top/ crosol mop/		Brill should be used with flat mop only			
5	scrubber drying direct method	Redur F Brill	3% 3 - 5%	_	d red/	Duomatic / Laser Mambo / Samba Sprinter / iMatic				
5	spray cleaning full spray	Polyspray Elfspray	100% 100%	P Pac		Monomatic DS / Spray unit	after polishing			

^{*} basic treatment / structure: B: coated / C: waxed / D: oiled / E: sealed / F: untreated / G: maintenance care product / P: polishing / S: structured / V: heavily soiled

no.27 Synthetic stone, polished, paving stones and Terrazzo



maintenance cleaning			object			date		
				address			customer	
work	process: select one work stage from	each nui	mber	room classif	icatio	n	representative	
П		frequ	recommendations			recommendations	recommendations	
₹	cleaning method	ency	* chemical products	s dosage	*	pad / brush / mop / cloth	machine / tool	comments
1	dusting damp mopping	[]			B F	Masslinn / Floorwit Masslinn 2000/Floorwit white	Balit Varifix/ Balit/	
2	chewing gum removal		Karpfrost Karpotek	100%				if needed
	cleaning without maintenance							
	wet mopping	r7	Ecofloor	0.5 - 1%		Mop Microbrush/	Wetbox system	^
3	wet mopping direct method		Reshine	1 - 2%		Micro-Mop Top/	Socar / Drewell	i i
	E/III direct metrica	'	Biosan	0.8 - 1.5%		Mop Variwet	Variwet / B. Varifix	
	scrubber drying	5	Ecofloor	0.5 - 1%		Microsol fibre pad/	Duomatic / Laser	^
3	direct method		Reshine	1 - 2%	_	Pad red/	Mambo / Samba	
	307 II	,	Libero	0.5 - 3%	V (Pad blue/	Sprinter / iMatic	
3	polishing, vacuum polishing				В (В (Pad Blue Ice/ US pad yellow/	Monomatic HS / Suction ring Monor Monomatic US /	after polishing
	cleaning with maintenance							
3	wet mopping direct method		Redur F Brill	1% 1 - 2%	F	Mop Microbrush/ Micro-Mop Top/ Flat mop/	Wetbox system Socar / Drewell Variwet / B. Varifix	Brill should be used with flat mop only
3	scrubber drying direct method		Redur F Brill	1% 1 - 2%	V	Microsol fibre pad/ Pad red/ Pad blue/	Duomatic / Laser Mambo / Samba Sprinter / iMatic	
3	spray cleaning partial spray		Polyspray Elfspray Polish	100% 100% 33%	P	Pad red/ Pad yellow/	Monomatic DS / Spray unit	after polishing
3	US spray cleaning partial spray		B US Restorer	100%	P	US pad pink/ US pad yellow/	Monomatic US / Spray unit	after polishing

^{*} basic treatment / structure: B: coated / C: waxed / D: oiled / E: sealed / F: untreated / G: maintenance care product / P: polishing / S: structured / V: heavily soiled

no.27 Synthetic stone, polished, paving stones and Terrazzo



interim cleaning		object		date			
					ddress	customer	
work process: select one work stage from each number room clas					ication	representative	
		frequ	recommendations		recommendations	recommendations	
7	cleaning method	encv	* chemical products	dosage	* pad / brush / mop / clo		comments
Ť					Masslinn 2000/Floorw		
1	dusting damp mopping				B Masslinn / Floorwit	Balit/	
	damp mopping	1			B Synthetic fur		
					S Dust roller nozzle	Monovac /	
1	dry vacuum cleaning)				Scuba	
		'					
	chewing gum	7	Karpfrost	100%			
2	removal		Karpotek				if needed
	1.40.000 to 1.000						
	cleaning without maintenance	_	Doobino	3 - 5%	Micro Mon Ton/	Socar / Drewell	
3	wet mopping	[777]	Reshine G Antiwax forte	3 - 5% 2 - 5%	Micro-Mop Top/		
3	wet mopping indirect method	التنا	G Antiwax forte	2 - 5%	Mop Microbrush/	Wetbox system	
			Reshine	3 - 5%	Microsol fibre pad/	Duomatic / Laser	
3	scrubber drying		G Antiwax forte	2 - 5%	Pad red/	Mambo / Samba	
	indirect method	للسلة			V Pad blue/	Sprinter / iMatic	
	wat manning	,	Biosan	3%	Micro-Mop Top/	Socar / Drewell	if needed, bad
4	wet mopping direct method				Mop Microbrush/	Wetbox system	smell could be
	direct method	1			Mop Variwet	Variwet / B. Varifix	removed with
	cleaning with maintenance						
	spray cleaning		Polyspray	100%	Pad red/	Monomatic DS /	
3	full spray		Elfspray	100%	P O Pad yellow/	Spray unit	after polishing
	Tan opray	'	Polish	33%			
	us spray cleaning	!7	B US Restorer	100%	US pad pink/	Monomatic US /	6 H. I.
3	full spray	<u> </u>			P US pad yellow/	Spray unit	after polishing
	_ · /						

^{*} basic treatment / structure: B: coated / C: waxed / D: oiled / E: sealed / F: untreated / G: maintenance care product / P: polishing / S: structured / V: heavily soiled

no.27 Synthetic stone, polished, paving stones and Terrazzo



	basic cleaning			object			_ date		_
				a	ddress	8	customer		
work	process: select one work stage from	each nui	mber	room classif	icatior	າ	representative		
	cleaning method	frequ ency	recommendations * chemical products	dosage	*	recommendations pad / brush / mop / cloth	recommendations machine / tool	comments	
1	dusting damp mopping				B F B	Masslinn / Floorwit Masslinn 2000/Floorwit white Synthetic fur	Balit Varifix/ Balit/		
1	dry vacuum cleaning	[]			S	Dust roller nozzle	Monovac / Scuba		
2	chewing gum removal	[]	Karpfrost Karpotek	100%				if needed	
	cleaning without maintenance								
3	wet scrubbing and wet vacuuming		B Remat forte B Relino Antiwax forte	10 - 20% 20 - 50% 30 - 50%		Microsol fibre pad/ Pad green/	Monomatic I / Watertank Duovac /		
3	scrubber drying indirect method		B Remat B Relino Antiwax forte	10 - 20% 20 - 50% 30 - 50%		Microsol fibre pad/ Pad green/	Duomatic / Laser Mambo / Samba Sprinter / iMatic	2 m	
4	rinsing		pure water			Microsol fibre pad/ Pad blue/	Monomatic I / Duovac / Duomatic / Laser		pH 7
5	wet mopping direct method		Biosan	3%		Micro-Mop Top/ Mop Microbrush/ Mop Variwet	Socar / Drewell Wetbox system Variwet / B. Varifix	if needed, bad smell could be removed with	

change pad often important:

green and black pad on hard stone only

Use a coin or a key to do a scratch test, to check if all the protective coating has been removed.

When white abrasion occurs, carry out a full clean to remove all the protective coating

For initial cleaning after basic cleaning, see "initial cleaning".

^{*} basic treatment / structure: B: coated / C: waxed / D: oiled / E: sealed / F: untreated / G: maintenance care product / P: polishing / S: structured / V: heavily soiled

no.27 Synthetic stone, polished, paving stones and Terrazzo



	protective treatment			object	date		-
			room classifi	Idress	customer		
work	process: select one work stage from each nur	nber	room classiii	<u></u>	representative		
	cleaning method	recommendations * chemical products	dosage	recommendations * pad / brush / mop / cloth	recommendations machine / tool	comments	
1	dusting damp mopping			Masslinn 2000/Floorwit white	Balit Varifix/ Balit/		
	pore filling (only if necessary)						
2	pore filling	Porosol	100%	Cover for Florfix Flat mop/	Florfix/ Drewell/ Buket plast 22l	If necessary, one layer on porous surface	
	coating						
3	coating	Stoner Mepol HM	100% 100%	Cover for Florfix Flat mop/	Florfix/ Drewell/ Buket plast 22l	1 - 3 thin layers	
3	waxing	Polish	100%	Cover for Florfix Flat mop/	Florfix/ Drewell/ Buket plast 22l	1 - 3 thin layers	
	buffing wax treatment (only if necessa	ry)					
4	dusting damp mopping			Masslinn 2000/Floorwit white	Balit Varifix/ Balit/	if needed	
4	polishing, vacuum polishing			C Pad yellow/	Monomatic HS / Suction ring Monon	after polishing	
	coating						
2	impregnation	Imprasol	100%	Cover for Florfix Flat mop/	Florfix/ Drewell/ Buket plast 22l	If necessary, one layer on porous surface	

before protective treatment: the floor must be perfectly stripped, thoroughly rinsed and completely dry! important:

Let dry protection treatment completely between the layers and before use

do not coat impregnated floors

Process treatement of protection: see descriptione of method

For initial cleaning with maintenance cleaner after protective treatment, see "initial cleaning".

^{*} basic treatment / structure: B: coated / C: waxed / D: oiled / E: sealed / F: untreated / G: maintenance care product / P: polishing / S: structured / V: heavily soiled



no.27 Synthetic stone, polished, paving stones and Terrazzo



Information about the flooring



Wetrok AG cannot accept any liability for damages due to improper use.

For security information, see the safety data sheet at www.wetrok.ch.

Wear protection: gloves, safety goggles, work clothes

Follow the information and remarks on the label, product data sheet and material safety data sheet.

The product data sheet describes the product and gives information about its application, storage. See www.wetrok.ch

The recommended colours of pad and brushes consist to the actual wWetrok product range

Follow the special cleaning and care instructions of the floor manufacturer

The cleaning and care instructions are recommendations and suggestions and apply to floorings in object quality.



Strong acids can destroy cement-bound synthetic stone.

Cement-bound synthetic stone is sensitive to solvents.

Most grouts are acid sensitive. Soak the joints well before using acidic cleaners.

There must be no coating in the open air and in wet rooms. Danger of slipping!

There must be no coating in the open air and in wet rooms. Danger of slipping!



Synthetic stone is a blend of coloured stone chippings in cement or bound with a resin.

Cast stone is laid as finished slabs and terrazzo is poured and ground across the entire surface.



Distinguishing feature: cement-bound synthetic stone acid assay: apply a little basic sanitary cleaner to the magnesite covering. Foams up: material damage!



Remove loose dirt before every cleaning, damp mop smooth floors and vacuum structured floors.

Cleaning agents and surface treatments may alter the appearance and properties of a floor's surface.

Test on an inconspicuous spot to find which product is suitable for your requirements.

Test beforehand on an inconspicuous spot to see if the cleaning agent or surface treatment damages the floor.

Dirt-trapping zones, incl. dirt-trapping mats (Wetrok Gardamat) in the entrance, at least 7m long, greatly reduce the amount of dirt tracked into the building.

If you have any questions, please don't hesitate to contact us.

For training courses, contact the Wetrok Academy, tel. +41 (0)43 255 51 43 or academy@wetrok.ch.

Wetrok AG Steinackerstrasse 62, CH-8302 Kloten, Tel +41 (0)43 255 51 51, info@wetrok.ch, www.wetrok.ch, www.wetrok.com