no.29 Natural stone, acid-resistant (polished)



cleaning system without treatment	object_	date	
end of construction	address	customer	
	room classification	representative	

work	work process: select one work stage from each number										
	7	recommendations			recommendations						
	cleaning method	* chemical products	dosage		machine / tool	comments					
					Twinvac /	large areas:					
1	dry vacuum cleaning			, , , , , , , , , , , , , , , , , , , ,	Duovac /	sweeping					
	Book - Astronomy			3	Silento /	1 0					
	dusting			Masslinn 2000/Floorwit white							
2	damp mopping			Multi squeegee/	Balit/						
	cleaning without maintenance care pro	duct (if coating follow	re)								
		Ecofloor	0.5 - 1%	Micro-Mop Top/	Socar / Drewell	A					
3	wet mopping direct method	V Reshine	3 - 5%	Microsol mop/	Jocai / Dieweii						
	direct method	Alcosal	1 - 2%	Willorddol Mop/							
		Ecofloor	0.5 - 1%	Microsol fibre pad/	Duomatic / Laser						
3	scrubber drying direct method	V Reshine	3 - 5%		Mambo / Samba						
	allect method	V Antiwax forte	2 - 5%		Sprinter / iMatic						
	wet scrubbing and	Reshine	3 - 5%	<u> </u>	Monomatic I /						
3	wet scrubbing and wet vacuuming	Antiwax forte	2 - 5%	_	Watertank	heavily soiled					
	= III				Duovac /						
	3 / Q		4.4			W and deal					
4	stain removal	See cleaning instruc	tion no 41			if needed					
	cleaning with maintenance care (first)	protective treatment wi	th same pro	duct as in maintenance cleaning)							
		Redur	3%		Socar / Drewell	A					
5	wet mopping direct method			Microsol mop/							
	direct method			·							
	scrubber drying	Redur	3%	Microsol fibre pad/	Duomatic / Laser						
5	direct method			Pad red/	Mambo / Samba						
	and in direct method				Sprinter / iMatic						
	spray cleaning	Polyspray	100%		Monomatic DS /						
5	full spray	Elfspray	100%	P O Pad yellow/	Spray unit	after polishing					

^{*} basic treatment / structure: B: coated / C: waxed / D: oiled / E: sealed / F: untreated / G: maintenance care product / P: polishing / S: structured / V: heavily soiled

no.29 Natural stone, acid-resistant (polished)



maintenance cleaning			object			date		
				address			customer	
work	process: select one work stage from	each nu	mber	room classif	ication	1	representative	
\bigcup	cleaning method	frequ ency	recommendations * chemical products	dosage	*	recommendations pad / brush / mop / cloth	recommendations machine / tool	comments
1	dusting damp mopping				В	Masslinn 2000/Floorwit white Synthetic fur	Balit Varifix/ Balit/	
2	chewing gum removal		Karpfrost Karpotek	100%				if needed
	cleaning without maintenance							
3	wet mopping direct method		Ecofloor Reshine Biosan	0.5 - 1% 1 - 2% 0.8 - 1.5%		Micro-Mop Top/ Mop Variwet	Wetbox system Socar / Drewell Variwet / B. Varifix	
3	scrubber drying direct method		Ecofloor Reshine Libero	0.5 - 1% 1 - 2% 0.5 - 3%	V	Microsol fibre pad/ Pad red/	Duomatic / Mambo / Samba Sprinter / iMatic	
3	polishing, vacuum polishing				В	Pad Blue Ice/ US pad yellow/	Monomatic HS / Monomatic US /	after polishing
	cleaning with maintenance							
3	wet mopping direct method		Redur	1%		Micro-Mop Top/ Mop Variwet	Wetbox system Socar / Drewell Variwet / B. Varifix	
3	scrubber drying direct method		Redur	1%	V	Microsol fibre pad/ Pad red/	Duomatic / Laser Mambo / Samba Sprinter / iMatic	
3	spray cleaning partial spray		Polyspray Elfspray	100% 100%	Р	Pad red/ Pad yellow/	Monomatic DS / Spray unit	after polishing
3	US spray cleaning partial spray		B US Restorer	100%	Р	US pad pink/ US pad yellow/	Monomatic US / Spray unit	after polishing

^{*} basic treatment / structure: B: coated / C: waxed / D: oiled / E: sealed / F: untreated / G: maintenance care product / P: polishing / S: structured / V: heavily soiled

no.29 Natural stone, acid-resistant (polished)



interim cleaning		objectaddress		date customer				
work	process: select one work stage from	each nu	mber	room classificati			representative	
	cleaning method	frequ ency	recommendations * chemical products	dosage	*	recommendations pad / brush / mop / cloth	recommendations machine / tool	comments
1	dusting damp mopping				В	Masslinn 2000/Floorwit white Synthetic fur	Balit Varifix/ Balit/	
1	dry vacuum cleanin	g []			V	Dust roller nozzle	Monovac / Scuba	
2	chewing gum removal		Karpfrost Karpotek	100%				if needed
	cleaning without maintenance							
3	wet mopping indirect method		Reshine G Rewit 2000	3 - 5% 2 - 5%		Micro-Mop Top/ Mop Microbrush/	Wetbox system Socar / Drewell	
3	scrubber drying indirect method		Reshine G Rewit 2000	3 - 5% 2 - 5%	v O	Microsol fibre pad/ Pad red/	Duomatic / Laser Mambo / Samba Sprinter / iMatic	
3	polishing, vacuum polishing					Pad Blue Ice/ Pad yellow/	Monomatic HS / Monomatic US /	after polishing
4	wet mopping direct method		Biosan	3%		Micro-Mop Top/ Mop Variwet	Socar / Drewell Wetcar / Drewell Variwet / B. Varifix	if needed, bad smell could be removed with
	cleaning with maintenance							
3	spray cleaning full spray		Polyspray Elfspray	100% 100%	Р	Pad red/ Pad yellow/	Monomatic DS / Spray unit	after polishing
3	spray cleaning full spray		B US Restorer	100%	P	US pad pink/ US pad yellow/	Monomatic US / Spray unit	after polishing

Sensitive or resistant against acid means against amidosulphuric acid important:

^{*} basic treatment / structure: B: coated / C: waxed / D: oiled / E: sealed / F: untreated / G: maintenance care product / P: polishing / S: structured / V: heavily soiled



no.29 Natural stone, acid-resistant (polished)



	basic cleaning				object		date	
work	work process: select one work stage from each number			room classif	ddres icatio		customer representative	
	cleaning method	frequ ency	recommendations * chemical products	dosage	*	recommendations pad / brush / mop / cloth	recommendations machine / tool	comments
1	dusting damp mopping				В	Masslinn 2000/Floorwit white Synthetic fur	Balit Varifix/ Balit/	
1	dry vacuum cleaning				V	Dust roller nozzle	Monovac / Scuba	
2	chewing gum removal		Karpfrost Karpotek	100%				if needed
	cleaning without maintenance							
3	wet scrubbing and wet vacuuming		Antiwax forte G Rewit 2000 B Relino	30 - 50% 10 - 20% 20 - 50%	V	Microsol fibre pad/ Pad red/ Pad blue/	Monomatic I / Duovac / Monomatic LS /	
3	scrubber drying indirect method		Antiwax forte G Rewit 2000 B Relino	30 - 50% 10 - 20% 20 - 50%		Microsol fibre pad/ Pad red/ Pad blue/	Duomatic / Laser Mambo / Samba Sprinter / iMatic	2 m
4	rinsing		pure water			Microsol fibre pad/ Pad red/	Monomatic I / Duovac / Duomatic / Laser	pH 7
5	stain removal		See cleaning instruct					if needed
6	wet mopping direct method		Biosan	3%		Micro-Mop Top/ Mop Variwet	Wetbox system Socar / Drewell Variwet / B. Varifix	if needed, bad smell could be removed with

Sensitive or resistant against acid means against amidosulphuric acid important: Use a coin or a key to do a scratch test, to check if all the protective coating has been removed.

^{*} basic treatment / structure: B: coated / C: waxed / D: oiled / E: sealed / F: untreated / G: maintenance care product / P: polishing / S: structured / V: heavily soiled



no.29 Natural stone, acid-resistant (polished)



	protective treatment		C	object	date		<u></u>	
			ad	dress	customer		_	
work	process: select one work stage from each nur	mber	room classific	cation	representative			
	cleaning method	recommendations * chemical products	dosage	recommendations * pad / brush / mop / cloth	recommendations machine / tool	comments		
1	dusting damp mopping			Masslinn 2000/Floorwit white	Balit Varifix/ Balit/			
	protective treatment							
2	impregnation	Imprasol	100%	Cover for Florfix Flat mop/	Florfix/ Drewell/ Buket plast 22l	apply first layer with care		
	coating							
2	coating	Stoner	100%	Cover for Florfix Flat mop/	Florfix/ Drewell/ Buket plast 22l	1 - 3 thin layers		
3	dusting damp mopping			Masslinn 2000/Floorwit white Synthetic fur	Balit Varifix / Balit/	if needed		

important: if needed

Sensitive or resistant against acid means against amidosulphuric acid

before protective treatment: the floor must be perfectly stripped, thoroughly rinsed and completely dry!

Let dry protection treatment completely between the layers and before use

do not coat impregnated floors

Process treatement of protection: see descriptione of method

For initial cleaning with maintenance cleaner after protective treatment, see "initial cleaning".

^{*} basic treatment / structure: B: coated / C: waxed / D: oiled / E: sealed / F: untreated / G: maintenance care product / P: polishing / S: structured / V: heavily soiled



no.29 Natural stone, acid-resistant (polished)



Information about the flooring



Wetrok AG cannot accept any liability for damages due to improper use.

For security information, see the safety data sheet at www.wetrok.ch.

Wear protection: gloves, safety goggles, work clothes

Follow the information and remarks on the label, product data sheet and material safety data sheet.

The product data sheet describes the product and gives information about its application, storage. See www.wetrok.ch

The recommended colours of pad and brushes consist to the actual wWetrok product range

Follow the special cleaning and care instructions of the floor manufacturer

The cleaning and care instructions are recommendations and suggestions and apply to floorings in object quality.



Hard types of stone, e.g. granite, queiss, quartzite and porphyry, are largely acid resistant.


Sensitive or resistant against acid means against amidosulphuric acid

The polish can be sensitive to acids or alkalines. Test in an inconspicuous place!

Most grouts are acid sensitive. Soak the joints well before using acidic cleaners.

Strong alkalines can attack polished stone coverings and destroy the shine.

There must be no coating in the open air and in wet rooms. Danger of slipping!



Soak the joints well or saturate them with an alkali cleaning solution before removing cement residue or limescale.

Spray cleaning only for small joints and flat surfaces; no fillet joints.

Natural stone is a 100% natural product consisting of minerals such as quartz, feldspar, calcite, selenite, hornblende or mica.

The colour and the appearance of the stone varies depending on its origin.

Distinguishing feature: natural stone acid-proof acid assay: apply a little basic sanitary cleaner to the stone covering, does not foam up.



Remove loose dirt before every cleaning, damp mop smooth floors and vacuum structured floors.

Cleaning agents and surface treatments may alter the appearance and properties of a floor's surface.

Test on an inconspicuous spot to find which product is suitable for your requirements.

Test beforehand on an inconspicuous spot to see if the cleaning agent or surface treatment damages the floor.

Dirt-trapping zones, incl. dirt-trapping mats (Wetrok Gardamat) in the entrance, at least 7m long, greatly reduce the amount of dirt tracked into the building.

If you have any questions, please don't hesitate to contact us.

For training courses, contact the Wetrok Academy, tel. +41 (0)43 255 51 43 or academy@wetrok.ch.

Wetrok AG Steinackerstrasse 62, CH-8302 Kloten, Tel +41 (0)43 255 51 51, info@wetrok.ch, www.wetrok.ch, www.wetrok.com