no. 32 Natural stone, acid-susceptible (polished)



cleaning system without treatment end of construction object address date customer

room classification

representative

work process: select one work stage from each number $\hfill \Box$

\mathbb{R}	cleaning method	recommendations * chemical products	dosage	recommendations * pad / brush / mop / cloth	recommendations machine / tool	comments
1	dry vacuum cleaning			Dust roller nozzle Neverclog filter without ring Filter bag with ring	Twinvac / Duovac / Silento /	large areas: sweeping
2	dusting damp mopping			Masslinn 2000/Floorwit white Multi squeegee/	Balit Varifix / Balit/	
	cleaning without maintenance care pro					
3	wet mopping direct method	Ecofloor V Reshine Alcosal	0.5 - 1% 3 - 5% 1 - 2%	Micro-Mop Top / Microsol mop/	Socar / Drewell	
3	scrubber drying direct method	Ecofloor V Reshine V Antiwax forte	0.5 - 1% 3 - 5% 2 - 5%	Microsol fibre pad/ V Pad red/	Duomatic / Laser Mambo / Samba Sprinter / iMatic	
3	wet scrubbing and wet vacuuming	Reshine Antiwax forte	3 - 5% 2 - 5%	Microsol fibre pad/ V Pad red/	Monomatic I / Watertank Duovac /	heavily soiled
4	stain removal	See cleaning instruct				if needed
	cleaning with maintenance care (first					
5	wet mopping direct method	Redur	3%	Micro-Mop Top / Microsol mop/	Socar / Drewell	
5	scrubber drying direct method	Redur	3%	Microsol fibre pad/ Pad red/	Duomatic / Laser Mambo / Samba Sprinter / iMatic	
5	spray cleaning full spray	Polyspray Elfspray	100% 100%	P Ad red/ P Pad yellow/	Monomatic DS / Spray unit	after polishing

* basic treatment / structure: B: coated / C: waxed / D: oiled / E: sealed / F: untreated / G: maintenance care product / P: polishing / S: structured / V: heavily soiled

no. 32 Natural stone, acid-susceptible (polished)



maintenance cleaning				object			date	
work process: select one work stage from each number				address room classification			customer representative	
	process. select one work stage from			TOOTT Classif	CallOII		· · · · · · · · · · · · · · · · · · ·	
	Cleaning method	frequ ency	recommendations* chemical products	dosage	*	recommendations pad / brush / mop / cloth	recommendations machine / tool	comments
1	dusting damp mopping				В	Masslinn 2000/Floorwit white Synthetic fur	Balit Varifix / Balit/	
2	chewing gum removal		Karpfrost Karpotek	100%				if needed
	cleaning without maintenance							
3	wet mopping direct method		Ecofloor Reshine Alcosal	0.5 - 1% 1 - 2% 1 - 2%		Micro-Mop Top / Micro-Mop Top/ Mop Variwet	Wetbox system Socar / Drewell Variwet / B. Varifix	
3	scrubber drying direct method		Ecofloor Reshine Libero	0.5 - 1% 1 - 2% 0.5 - 3%	v 🔴	Microsol fibre pad/ Pad red/	Duomatic / Mambo / Samba Sprinter / iMatic	
3	polishing, vacuum polishing				в 🔵 в 🔴	Pad Blue Ice/ US pad yellow/	Monomatic HS / Suction ring Monor Monomatic US /	after polishing
	cleaning with maintenance							
3	wet mopping direct method		Redur	1%		Micro-Mop Top / Micro-Mop Top/ Mop Variwet	Wetbox system Socar / Drewell Variwet / B. Varifix	
3	scrubber drying direct method		Redur	1%	> (Microsol fibre pad/ Pad red/	Duomatic / Laser Mambo / Samba Sprinter / iMatic	
3	spray cleaning partial spray		Polyspray Elfspray	100% 100%	Р 🔵	Pad red/ Pad yellow/	Monomatic DS / Spray unit	after polishing
3	US spray cleaning partial spray		B US Restorer	100%	P) US pad pink /) US pad yellow/	Monomatic US / Spray unit	after polishing

* basic treatment / structure: B: coated / C: waxed / D: oiled / E: sealed / F: untreated / G: maintenance care product / P: polishing / S: structured / V: heavily soiled

important: Ser

nt: Sensitive or resistant against acid means against amidosulphuric acid

no. 32 Natural stone, acid-susceptible (polished)



interim cleaning			object			date		
			address			customer		
work	process: select one work stage from	each nu	mber	room classif	ication		representative	
R	cleaning method step	frequ ency	recommendations * chemical products	dosage	*	recommendations pad / brush / mop / cloth	recommendations machine / tool	comments
1	dusting damp mopping				В	Masslinn 2000/Floorwit white Synthetic fur	Balit Varifix / Balit/	
1	dry vacuum cleaning				V	Dust roller nozzle	Monovac / Scuba	
2	chewing gum removal	 	Karpfrost Karpotek	100%				if needed
	cleaning without maintenance							
3	wet mopping indirect method		Reshine G Rewit 2000	3 - 5% 2 - 5%		Micro-Mop Top / Mop Microbrush/	Wetbox system Socar / Drewell	
3	scrubber drying indirect method		Reshine G Rewit 2000	3 - 5% 2 - 5%) Microsol fibre pad / Pad red/	Duomatic / Laser Mambo / Samba Sprinter / iMatic	$\bigcirc \land$
3	stain removal		See cleaning instruc	tion no 41				if needed
3	polishing, vacuum polishing				в 🔵 в 🦲	Pad Blue Ice/ US pad yellow/	Monomatic HS / Suction ring Monor Monomatic US /	after polishing
	cleaning with maintenance							
3	spray cleaning full spray		Polyspray Elfspray	100% 100%	Р 🦲	Pad red/ Pad yellow/	Monomatic DS / Spray unit	after polishing
3	spray cleaning		B US Restorer	100%	P) US pad pink /) US pad yellow/	Monomatic US / Spray unit	after polishing

* basic treatment / structure: B: coated / C: waxed / D: oiled / E: sealed / F: untreated / G: maintenance care product / P: polishing / S: structured / V: heavily soiled

important: Sensitive or resistant against acid means against amidosulphuric acid

no. 32 Natural stone, acid-susceptible (polished)



	basic cleaning			object		date	
work	process: select one work stage from each r	number	ad room classifi	dress cation		customer representative	
R	freq cleaning method ency		s dosage	*	recommendations pad / brush / mop / cloth	recommendations machine / tool	comments
1	dusting damp mopping			В	Masslinn 2000/Floorwit white Synthetic fur	Balit Varifix / Balit/	
1	dry vacuum cleaning			V	Dust roller nozzle	Monovac / Scuba	
2	chewing gum removal	Karpfrost Karpotek	100%				if needed
	cleaning without maintenance						
3	wet scrubbing and wet vacuuming	Antiwax forte G Rewit 2000 B Relino	30 - 50% 10 - 20% 20 - 50%	в	Microsol fibre pad/ Pad red/ Pad blue/	Monomatic I / Watertank Duovac /	
3	scrubber drying indirect method	Antiwax forte G Rewit 2000 B Relino	30 - 50% 10 - 20% 20 - 50%	в	Microsol fibre pad/ Pad red/ Pad blue/	Duomatic / Laser Mambo / Samba Sprinter / iMatic	
4	rinsing	pure water) Microsol fibre pad / Pad red/	Monomatic I / Duovac / Duomatic / Laser	рН 7
5	stain removal	See cleaning instruc	ction no 41				if needed
6	wet mopping direct method	Biosan	3%		Micro-Mop Top / Micro-Mop Top/ Mop Variwet	Wetbox system Socar / Drewell Variwet / B. Varifix	if needed, bad smell could be removed with

* basic treatment / structure: B: coated / C: waxed / D: oiled / E: sealed / F: untreated / G: maintenance care product / P: polishing / S: structured / V: heavily soiled

important: For initial cleaning after basic cleaning, see "initial cleaning".

Use a coin or a key to do a scratch test, to check if all the protective coating has been removed.

no. 32 Natural stone, acid-susceptible (polished)



protective treatment				object	date		
			ac	ddress	customer		
work	process: select one work stage from each nur	nber r	oom classifi	ication	representative		
		recommendations		recommendations	recommendations		
いと	cleaning method	* chemical products	dosage	* pad / brush / mop / cl	oth machine / tool	comments	
1	dusting damp mopping			Masslinn 2000/Floorv	vit white Balit Varifix/ Balit/		
	coating						
2	coating	Stoner	100%	Cover for Florfix Flat mop/	Florfix/ Drewell/	If necessary, one layer on porous surface	

* basic treatment / structure: B: coated / C: waxed / D: oiled / E: sealed / F: untreated / G: maintenance care product / P: polishing / S: structured / V: heavily soiled

important: if needed

Sensitive or resistant against acid means against amidosulphuric acid before protective treatment: the floor must be perfectly stripped, thoroughly rinsed and completely dry! Let dry protection treatment completely between the layers and before use do not coat impregnated floors Process treatement of protection: see descriptione of method

For initial cleaning with maintenance cleaner after protective treatment, see "initial cleaning".

no. 32 Natural stone, acid-susceptible (polished)



Information about the flooring



Wetrok AG cannot accept any liability for damages due to improper use.
For security information, see the safety data sheet at www.wetrok.ch.
Wear protection: gloves, safety goggles, work clothes
Follow the information and remarks on the label, product data sheet and material safety data sheet.
The product data sheet describes the product and gives information about its application, storage. See www.wetrok.ch
The recommended colours of pad and brushes consist to the actual wWetrok product range
Follow the special cleaning and care instructions of the floor manufacturer
The cleaning and care instructions are recommendations and suggestions and apply to floorings in object guality.



Soft stone, e.g. marble, limestone (Jura-limestone, concha-limestone), Solnhofer stone, travertine, slate or sandstone is sensitive to acid.
Sensitive or resistant against acid means against amidosulphuric acid
The polish can be sensitive to acids or alkalines. Test in an inconspicuous place!
Most grouts are acid sensitive. Soak the joints well before using acidic cleaners.
Strong alkalines can attack polished stone coverings and destroy the shine.
Soft stone is sensitive to scratches, only use suitable pads and brushes.
There must be no coating in the open air and in wet rooms. Danger of slipping!
Fats and oils can penetrate into the stone covering. Stain formation!
Soak the joints well or saturate them with an alkali cleaning solution before removing cement residue or limescale .
Spray cleaning only for small joints and flat surfaces; no fillet joints.
Natural stone is a 100% natural product consisting of minerals such as quartz, feldspar, calcite, selenite, hornblende or mica.
The colour and the appearance of the stone varies depending on its origin.
Distinguishing feature: natural stone acid-proof acid assay: basic sanitary cleaner foams up: material damage!



Remove loose dirt before every cleaning, damp mop smooth floors and vacuum structured floors. Cleaning agents and surface treatments may alter the appearance and properties of a floor's surface. Test on an inconspicuous spot to find which product is suitable for your requirements. Test beforehand on an inconspicuous spot to see if the cleaning agent or surface treatment damages the floor. Dirt-trapping zones, incl. dirt-trapping mats (Wetrok Gardamat) in the entrance, at least 7m long, greatly reduce the amount of dirt tracked into the building.

If you have any questions, please don't hesitate to contact us. For training courses, contact the Wetrok Academy, tel. +41 (0)43 255 51 43 or academy@wetrok.ch.

Wetrok AG Steinackerstrasse 62, CH-8302 Kloten, Tel +41 (0)43 255 51 51, info@wetrok.ch, www.wetrok.ch, www.wetrok.com