

General instructions for cleaning and care

no. 42 Removal of cement smears and limescale (description of method)



acid sensitive, scratch sensitive stone floors

object _____

date _____























































address _____

customer _____

room classification _____

representative _____

work process: select one work stage from each number

	cleaning method	freq uenc	* recommendations chemical products	dosage	* recommendations pad / brush / mop / cloth	recommendations machine / tool	comments
1	 dusting damp mopping				V Masslinn 2000 Multi squeegee	Balit with pad sole	
1	 dry vacuum cleaning				V S Dust roller nozzle V Combi-nozzle	Twinvac Monovac Portovac	heavily soiled
cleaning without maintenance							
2	 wet scrubbing and wet vacuuming		Polex Rewit 2000	0.5 - 1% 0.5 - 1%	 Microsol fibre pad  Pad red S  Scrubbing brush Filament	Monomatic I / LS Watertank Twinvac / Duovac	 
3	 wet scrubbing and wet vacuuming		Calexan	100%	 Microsol fibre pad  Pad red S  Scrubbing brush Filament	Monomatic I / LS Twinvac / Duovac	attention: modification of surface   
4	 rinsing		0	100%	 Microsol fibre pad  Pad red S  Scrubbing brush Filament	Monomatic I / LS Watertank Twinvac / Duovac	large areas: scrubber-dryer.  
4	 rinsing		0	100%	 Microsol fibre pad  Pad red S  Scrubbing brush Filament	Duo- / Discomatic Sprinter / Drivematic	large areas  
5	 wet scrubbing and wet vacuuming		Polex Rewit 2000	0.5 - 1% 0.5 - 1%	 Microsol fibre pad  Pad red S  Scrubbing brush Filament	Monomatic I / LS Watertank Twinvac / Duovac	
6	 rinsing		0	100%	 Microsol fibre pad  Pad red S  Scrubbing brush Filament	Monomatic I / LS Watertank Twinvac / Duovac	large areas: scrubber-dryer.  
6	 rinsing		0	100%	 Microsol fibre pad  Pad red S  Scrubbing brush Filament	Duo- / Discomatic Sprinter / Drivematic	large areas  

* basic treatment / structure: B: coated / C: waxed / D: oiled / E: sealed / F: untreated / G: maintenance care product / H: Disinfection / P: polishing / S: structured / V: heavily soiled

important: Wet scrubbing 1 minute at most with sanitairy basic cleaner, wet vacuuming instantly and rinse well. Repeat several times if needed.

General instructions for cleaning and care

no. 42 Removal of cement smears and limescale (description of method)



acid resistant and scratch sensitive stone floors

object _____

date _____


































address _____

customer _____

room classification _____

representative _____

work process: select one work stage from each number

↓	cleaning method		freq	recommenda	dosage	recommenda	recommenda	comments
			uenc	* chemical products		* pad / brush / mop / cloth	machine / tool	
1		dry vacuum cleaning	<input type="checkbox"/>			V S Dust roller nozzle V Combi-nozzle	Twinvac Monovac Portavac	heavily soiled
1		dusting damp mopping	<input type="checkbox"/>			Masslinn 2000	Balit with pad sole	
cleaning without maintenance								
2		wet mopping direct method	<input type="checkbox"/>	0	100%	Kentucky-mop		watering gouging. 
3		wet scrubbing and wet vacuuming	<input type="checkbox"/>	Calexan	100%	 Microsol fibre pad  Pad red S  Scrubbing brush Filament	Monomatic I / LS Twinvac / Duovac	  
4		rinsing	<input type="checkbox"/>	0	100%	 Microsol fibre pad  Pad red S  Scrubbing brush Filament	Monomatic I / LS Watertank Twinvac / Duovac	large areas: scrubber-dryer. pH 7 
4		rinsing	<input type="checkbox"/>	0	100%	 Microsol fibre pad  Pad red S  Scrubbing brush Filament	Duo- / Discomatic Sprinter / Drivematic	large areas pH 7 
5		wet scrubbing and wet vacuuming	<input type="checkbox"/>	Polex	0.5 - 1%	 Microsol fibre pad  Pad red S  Scrubbing brush Filament	Monomatic I / LS Watertank Twinvac / Duovac	
6	  	rinsing	<input type="checkbox"/>	0	100%	 Microsol fibre pad  Pad red S  Scrubbing brush Filament	Monomatic I / LS Twinvac / Duovac Duo- / Discomatic	large areas: scrubber-dryer. pH 7 

* basic treatment / structure: B: coated / C: waxed / D: oiled / E: sealed / F: untreated / G: maintenance care product / H: Disinfection / P: polishing / S: structured / V: heavily soiled

important: Wet scrubbing 1 minute at most with sanitairy basic cleaner, wet vacuuming instantly and rinse well. Repeat several times if needed.
Sensitive or resistant against acid means against amidosulphuric acid.

General instructions for cleaning and care

no. 42 Removal of cement smears and limescale (description of method)



acid and scratch resistant stone floors

object _____

date _____






































address _____

customer _____

room classification _____

representative _____

work process: select one work stage from each number

	cleaning method	freq uenc	recommendations chemical products	dosage	* recommendations pad / brush / mop / cloth	recommendations machine / tool	comments
1	 dry vacuum cleaning	<input type="checkbox"/>			V S Dust roller nozzle V Combi-nozzle	Twinvac Monovac Portavac	heavily soiled
1	 dusting damp mopping	<input type="checkbox"/>			Masslinn 2000	Balit with pad sole	
cleaning without maintenance							
2	 wet mopping direct method	<input type="checkbox"/>	0	100%	Kentucky-mop		watering gouging. 
3	 wet scrubbing and wet vacuuming	<input type="checkbox"/>	Calexan	100%	 Microsol fibre pad V  Pad green S  Scrubbing brush Filament	Monomatic I / LS Twinvac / Duovac	  
4	 rinsing	<input type="checkbox"/>	0	100%	 Microsol fibre pad V  Pad green S  Scrubbing brush Filament	Monomatic I / LS Watertank Twinvac / Duovac	large areas: scrubber-dryer.  
4	 rinsing	<input type="checkbox"/>	0	100%	 Microsol fibre pad V  Pad green S  Scrubbing brush Filament	Duo- / Discomatic Sprinter / Drivematic	large areas  
5	 wet scrubbing and wet vacuuming	<input type="checkbox"/>	Polex	0.5 - 1%	 Microsol fibre pad V  Pad green S  Scrubbing brush Filament	Monomatic I / LS Watertank Twinvac / Duovac	
6	rinsing   	<input type="checkbox"/>	0	100%	 Microsol fibre pad V  Pad green S  Scrubbing brush Filament	Monomatic I / LS Twinvac / Duovac Duo- / Discomatic	large areas: scrubber-dryer.  

* basic treatment / structure: B: coated / C: waxed / D: oiled / E: sealed / F: untreated / G: maintenance care product / H: Disinfection / P: polishing / S: structured / V: heavily soiled

important: Wet scrub for max 5 minutes with a sanitary basic cleaner then immediately wet vacuum and rinse well. Repeat several times if required.
Sensitive or resistant against acid means against amidosulphuric acid.

General instructions for cleaning and care



no. 42 Removal of cement smears and limescale (description of method)


Information about the flooring



Wetrot AG cannot accept any liability for damages due to improper use.
For security information, see the safety data sheet at www.wetrot.com.
Wear protection: gloves, safety goggles, work clothes.
Follow the information and remarks on the label, product data sheet and material safety data sheet.
The product data sheet describes the product and gives information about its application, storage. See www.wetrot.com.
The recommended colours of pad and brushes consist to the actual wWetrot product range.
Follow the special cleaning and care instructions of the floor manufacturer.
The cleaning and care instructions are recommendations and suggestions and apply to floorings in object quality.



Most grouts are acid sensitive. Soak the joints well before using acidic cleaners.
Strong acids can destroy limestone, slate and cement-bonded artificial stone.
Strong alkalines can attack polished stone coverings and destroy the shine.
Abrasive pads and brushes can destroy polishes, limestone, slate and cement-bonded artificial stone.
Plastic-bonded synthetic stone is sensitive to solvents.



Synthetic stone is a blend of coloured stone chippings in cement or bound with a resin.
Natural stone is a 100% natural product consisting of minerals such as quartz, feldspar, calcite, selenite, hornblende or mica.
Hard types of stone, e.g. granite, gneiss, quartzite and porphyry, are largely acid resistant.
Soft stone, e.g. marble, limestone (Jura-limestone, concha-limestone), Solnhofen stone, travertine, slate or sandstone is sensitive to acid.
Sensitive or resistant against acid means against amidosulphuric acid.
The colour and the appearance of the stone varies depending on its origin.
Cast stone is laid as finished slabs and terrazzo is poured and ground across the entire surface.
Distinguishing feature: cement-bound synthetic stone acid assay: apply a little basic sanitary cleaner to the magnesite covering. Foams up: material damage!



Remove loose dirt before every cleaning, damp mop smooth floors and vacuum structured floors.
Cleaning agents and surface treatments may alter the appearance and properties of a floor's surface.
Test on an inconspicuous spot to find which product is suitable for your requirements.
Test beforehand on an inconspicuous spot to see if the cleaning agent or surface treatment damages the floor.
Dirt-trapping zones, incl. dirt-trapping mats (Wetrot Gardamat) in the entrance, at least 7m long, greatly reduce the amount of dirt tracked into the building.

If you have any questions, please don't hesitate to contact us.
For training courses, contact the Wetrot Academy, tel. +41 (0)43 255 51 43 or academy@wetrot.ch.