

General instructions for cleaning and care



no. 43 Foam cleaning (walls e.g.showers)



cleaning system without treatment maintenance cleaning

object _____

date _____

address _____

customer _____

room classification _____

representative _____

work process: select one work stage from each number

↓ cleaning method	freq uenc	* recommendations chemical products	dosage	* recommendations pad / brush / mop / cloth	recommendations machine / tool	comments
1	<input type="checkbox"/>	Karpfrost Karpotek	100% 100%			if needed
cleaning without maintenance						
2	<input type="checkbox"/>		0 100%		Fixofoam	watering gouging.
3	<input type="checkbox"/>	Reofom Ketovapor Brilliant	3 - 5% 3 - 5%	<input checked="" type="checkbox"/> Microsol fibre pad for edges <input type="checkbox"/> Edge cleaning tool <input type="checkbox"/> Maxi-pad white	Fixofoam SmartFoam 3 SmartFoam 1	top down
4	<input type="checkbox"/>	Klares Wasser	100%		Fixofoam SmartSpray 5	pH 7
5	<input type="checkbox"/>	Calefom Ketacid Brilliant	3 - 5% 3 - 5%	<input checked="" type="checkbox"/> Microsol fibre pad for edges <input type="checkbox"/> Edge cleaning tool <input type="checkbox"/> Maxi-pad white	Fixofoam SmartFoam 3 SmartFoam 1	if needed
6	<input type="checkbox"/>	Klares Wasser	100%	Star window cleaner	Fixofoam SmartSpray 5	if needed
7	<input type="checkbox"/>				Floor squeegee Multi squeegee Star window cleaner	if needed

* basic treatment / structure: B: coated / C: waxed / D: oiled / E: sealed / F: untreated / G: maintenance care product / H: Disinfection / P: polishing / S: structured / V: heavily soiled

General instructions for cleaning and care



no. 43 Foam cleaning (walls e.g.showers)



interim cleaning

object _____
 address _____
 room classification _____
 date _____
 customer representative _____

work process: select one work stage from each number

↓ cleaning method	freq uenc	recommendations chemical products	dosage	recommendations pad / brush / mop / cloth	recommendations machine / tool	comments
1 chewing gum removal <input type="checkbox"/>		Karpfrost Karpotek	100% 100%			if needed

cleaning without maintenance

2 spraying <input type="checkbox"/>	0 <input type="checkbox"/>	100%		Fixofoam SmartSpray 5	watering gouging.	
3 foam cleaning <input type="checkbox"/>	Reofom Ketovapor Foam3	5% 3 - 5%	<input checked="" type="checkbox"/> Microsol fibre pad for edges <input type="checkbox"/> Edge cleaning tool <input type="checkbox"/> Maxi-pad white	Fixofoam SmartFoam 3 SmartFoam 1	top down 	
4 rinsing <input type="checkbox"/>	Klares Wasser	100%		Fixofoam SmartSpray 5	 	
5 foam cleaning <input type="checkbox"/>	Calefom Ketacid Foam3	5% 3 - 5%	<input checked="" type="checkbox"/> Microsol fibre pad for edges <input type="checkbox"/> Edge cleaning tool <input type="checkbox"/> Maxi-pad white	Fixofoam SmartFoam 3 SmartFoam 1	if needed 	
6 rinsing <input type="checkbox"/>	Klares Wasser	100%		Fixofoam SmartSpray 5	if needed 	
7 drying <input type="checkbox"/>				Floor squeegee Multi squeegee Star window cleaner	if needed 	

* basic treatment / structure: B: coated / C: waxed / D: oiled / E: sealed / F: untreated / G: maintenance care product / H: Disinfection / P: polishing / S: structured / V: heavily soiled

General instructions for cleaning and care



no. 43 Foam cleaning (walls e.g.showers)



basic cleaning

object _____
 address _____
 room classification _____
 date _____
 customer representative _____

cleaning method	freq uenc	recommendations chemical products	dosage	recommendations pad / brush / mop / cloth	recommendations machine / tool	comments
1 chewing gum removal <input type="checkbox"/>		Karpfrost Karpotek	100% 100%			if needed

cleaning without maintenance						
2 spraying <input type="checkbox"/>	0	100%		Fixofoam SmartSpray 5	watering gouging.	
3 foam cleaning <input type="checkbox"/>	Ketovapor Foam3	5%	<input checked="" type="checkbox"/> Microsol fibre pad for edges <input checked="" type="checkbox"/> Edge cleaning tool <input type="checkbox"/> Maxi-pad white	Fixofoam SmartFoam 3 SmartFoam 1	top down 	
4 rinsing <input type="checkbox"/>	Klares Wasser	100%		Fixofoam SmartFoam 3 SmartFoam 1	 	
5 foam cleaning <input type="checkbox"/>	Ketacid Foam3	5%	<input checked="" type="checkbox"/> Microsol fibre pad for edges <input checked="" type="checkbox"/> Edge cleaning tool <input type="checkbox"/> Maxi-pad white	Fixofoam SmartFoam 3 SmartFoam 1	top down 	
6 rinsing <input type="checkbox"/>	Klares Wasser	100%		Fixofoam SmartSpray 5	 	
7 drying <input type="checkbox"/>				Floor squeegee Multi squeegee Star window cleaner	 	

General instructions for cleaning and care



no. 43 Foam cleaning (walls e.g.showers)



Information about the flooring



Wetrok AG cannot accept any liability for damages due to improper use.

For security information, see the safety data sheet at www.wetrok.com.

Wear protection: gloves, safety goggles, work clothes.

Follow the information and remarks on the label, product data sheet and material safety data sheet.

The product data sheet describes the product and gives information about its application, storage. See www.wetrok.com.

The recommended colours of pad and brushes consist to the actual wWetrok product range.

Follow the special cleaning and care instructions of the floor manufacturer.

The cleaning and care instructions are recommendations and suggestions and apply to floorings in object quality.




Ceramic floor coverings are generally acid resistant.

Most grouts are acid sensitive. Soak the joints well before using acidic cleaners.

The glaze is sensitive to scratching. Do not use abrasive pads or brushes!

Souring can cause discolouration in the glaze. Check the glaze for acid resistance beforehand.

Do not use maintenance products on glazed tiles.



Ceramic floor coverings are heterogeneous products made from clay and aggregates such as feldspar and fluorite.

The higher the firing temperature and the longer the time spent in the oven, the denser and more strongly sintered the ceramic will be.

Earthenware: high water absorption (approx. 1,000°C), glazed earthenware: low water absorption (1,300°C).

Fine stoneware: unglazed stoneware with high strength and low porosity (low water absorption: < 0.5%).

The glaze is melted in a second firing.

Slip resistance in commercial areas: classification R9 - R13 (low to very high) and V4 - V10, in bare foot areas A,B,C.

Glazed stone product tiles are divided into 5 groups of different load-bearing capacities. Wear resistance groups I to V (very light to heavy load).

Scratch hardness: tiles with varying resistance to scratches, DIN 3 - 9 on the Mohs scale (satisfactory to good).



Remove loose dirt before every cleaning, damp mop smooth floors and vacuum structured floors.

Cleaning agents and surface treatments may alter the appearance and properties of a floor's surface.

Test on an inconspicuous spot to find which product is suitable for your requirements.

Test beforehand on an inconspicuous spot to see if the cleaning agent or surface treatment damages the floor.

Dirt-trapping zones, incl. dirt-trapping mats (Wetrok Gardamat) in the entrance, at least 7m long, greatly reduce the amount of dirt tracked into the building.

If you have any questions, please don't hesitate to contact us.

For training courses, contact the Wetrok Academy, tel. +41 (0)43 255 51 43 or academy@wetrok.ch.