no. 52 Wood parquet (oiled)



cleaning system with treatment end of construction object address

room classification

customer representative

date

work process: select one work stage from each number

		recommendations	deeege	*	recommendations	recommendations	o o m m o n i o
	cleaning method	* chemical products	dosage		pad / brush / mop / cloth Dust roller nozzle	machine / tool Twinvac /	comments
1	dry vacuum cleaning				Neverclog filter without ring	Duovac /	
					Filter bag with ring	Silento /	
	vacuum sweeping				<u> </u>	Speedmatic Twister	large areas: 2
1	sweeping					Turbo Sweep	sweeping m
	dusting				Masslinn 2000/Floorwit white		
2	damp mopping			V	Multi squeegee/	Balit/	
	cleaning without maintenance						
	wet mopping	Antiwax forte	2 - 5%		Mop Microbrush/	Socar / Drewell	
3	wet mopping direct method	Polex	2 - 4%		Microsol mop/		T 🔼
	scrubber drying	Antiwax forte	2 - 5%		Pad red/	Duomatic / Laser	
3	direct method	Polex	2 - 4%	V 🔘	Pad blue/	Mambo / Samba	
		Antiwax forte	2 - 5%		Pad red/	Sprinter / iMatic Monomatic I /	
3	wet scrubbing and	Polex	2 - 3% 2 - 4%	l v 🕇	Pad blue/	Watertank	heavily soiled 🛛 🐳 😡 🙏
J	wet vacuuming	I DIEX	2 - 470			Duovac /	
4	drying					Duovuo /	
	impregnation (only if necessary)						
5	oiling	See cleaning instruction	on no 61				if needed

* basic treatment / structure: B: coated / C: waxed / D: oiled / E: sealed / F: untreated / G: maintenance care product / P: polishing / S: structured / V: heavily soiled

no.52 Wood parquet (oiled)



maintenance cleaning				object address			date customer	
work	process: select one work stage from	each nur	nber	room classifi			representative	
R	cleaning method	frequ ency	recommendations * chemical products	dosage	*	recommendations pad / brush / mop / cloth	recommendations machine / tool	comments
1	dusting damp mopping					Masslinn / Floorwit Synthetic fur	Balit Varifix / Balit/	
1	vacuum sweeping sweeping						Speedmatic Twister Turbo Sweep	large areas: 2 sweeping m
2	chewing gum removal		Karpfrost Karpotek	100%				if needed
	cleaning without maintenance	(only if			iled 10			
3	wet mopping direct method		Polex	0.5 - 1%	v	Mop Sensitive Microsol mop/ Flat mop/	Wetbox system Socar / Drewell Variwet / B. Varifix	Ť
3	scrubber drying direct method		Polex Libero	0.5 - 1% 0.5 - 3%	v 🗧	Pad red/ Pad blue/	Duomatic / Laser Mambo / Samba Sprinter / iMatic	Ť
	cleaning with maintenance							
3	wet mopping direct method		Redur	1%	v	Mop Sensitive Microsol mop/ Flat mop/	Wetbox system Socar / Drewell Variwet / B. Varifix	
3	scrubber drying direct method		Redur	1%	v	Pad red/ Pad blue/	Duomatic / Laser Mambo / Samba Sprinter / iMatic	
3	spray cleaning partial spray		Leinol NW Polyspray	25 - 50% 100%	P O	Pad red/ Pad yellow/ Pad blue/	Monomatic DS / Spray unit	after polishing

* basic treatment / structure: B: coated / C: waxed / D: oiled / E: sealed / F: untreated / G: maintenance care product / P: polishing / S: structured / V: heavily soiled

important:

: oiling (6 - 8 times in first year, then as needed) When spray cleaning, you should change your pad often

no.52 Wood parquet (oiled)



interim cleaning object date address customer work process: select one work stage from each number room classification representative recommendations recommendations recommendations freau cleaning method chemical products dosage pad / brush / mop / cloth machine / tool comments encv Masslinn / Floorwit **Balit Varifix/** dustina 1 Balit/ damp mopping V Dust roller nozzle Monovac / large areas: dry vacuum cleaning 1 Scuba sweeping Karpfrost 100% chewing gum 2 if needed Karpotek removal Pad red/ Leinol NW 25 - 50% **Brush Bov** 3 stain removal v 🔘 Pad areen/ cleaning without maintenance Mop Microbrush/ Wetbox system Antiwax forte 2 - 5% wet mopping **B** 4 Rewit 2000 2 - 5% Microsol mop/ Socar / Drewell indirect method Antiwax forte 2 - 5% Pad blue/ **Duomatic / Laser** scrubber drying Microsol fibre pad/ 2 - 5% Mambo / Samba 4 Rewit 2000 indirect method Pad green/ v (Sprinter / iMatic Leinol NW 25 - 50% Pad red/ Monomatic DS / spray cleaning P Pad yellow/ after polishing Spray unit 4 Polyspray 100% full spray Monomatic HS / cleaning with maintenance Leinol NW 25 - 50% Pad blue/ Monomatic DS / spray cleaning Pad vellow/ polish when drv 4 Р 🔵 Spray unit full sprav Pad green/ ν (Balit Varifix/ Masslinn / Floorwit dusting 5 Balit/ damp mopping

* basic treatment / structure: B: coated / C: waxed / D: oiled / E: sealed / F: untreated / G: maintenance care product / P: polishing / S: structured / V: heavily soiled

important: oiling (6 - 8 times in first year, then as needed)

no.52 Wood parquet (oiled)

basic cleaning



date

customer

representative

work process: select one work stage from each number

room classification

object

address

Ē.	1							
R	cleaning method	frequ ency	recommendations * chemical products	dosage	*	recommendations pad / brush / mop / cloth	recommendations machine / tool	comments
1	dusting damp mopping	,				Masslinn / Floorwit	Balit Varifix / Balit/	
1	dry vacuum cleaning				V	Dust roller nozzle	Monovac / Scuba	
2	chewing gum removal		Karpfrost Karpotek	100%				if needed
	cleaning without maintenance							
3	dry sanding				v	 Pad green/ Microsol fibre pad/ Pad black/ 	Monomatic I / Suction ring Monor Monomatic LS /	after sanding, dry scrubbing
3	wet scrubbing and wet vacuuming		Antiwax forte	30 - 50%	V	 Pad green/ Microsol fibre pad/ Pad black/ 	Monomatic I / Watertank Duovac /	→
3	scrubber drying indirect method		Antiwax forte	30 - 50%		 Pad green/ Microsol fibre pad/ 	Duomatic / Laser Mambo / Samba Sprinter / iMatic	m ² 🔆 🚡 🚱 📐
4	rinsing		pure water) Pad blue /) Microsol fibre pad/	Monomatic I / Duovac / Duomatic / Laser	after spray cleaning nc 并 рн 7
3	spray cleaning full spray		Antiwax forte	30 - 50%	v S	9 Pad blue / 9 Pad green/	Monomatic I / Spray unit Monomatic LS /	

* basic treatment / structure: B: coated / C: waxed / D: oiled / E: sealed / F: untreated / G: maintenance care product / P: polishing / S: structured / V: heavily soiled

important:

change pad often After basic cleaning, protective treatment is necessary! green and black pad on hard wood only

no.52 Wood parquet (oiled)



protective treatment			object dress		date customer		_
	process: select one work stage from each nur				representative		
	cleaning method	recommendations * chemical products dosage	*	recommendations pad / brush / mop / cloth	recommendations machine / tool	comments	
1	dusting damp mopping			Masslinn 2000/Floorwit white	Balit Varifix / Balit/		
1	dry vacuum cleaning		S	Dust roller nozzle	Duovac / Scuba		
2	dry sanding		V	 Pad green/ Pad blue/ Pad black/ 	Monomatic HS / Suction ring	fine sanding	
3	dusting damp mopping			Masslinn 2000/Floorwit white	Balit Varifix / Balit/		
	pore filling (only if necessary)						
4	oiling	See cleaning instruction no 61					
	Change the system						
4	waxing	See cleaning instruction no 43				waxed parquet cannot be oiled afterwards	

* basic treatment / structure: B: coated / C: waxed / D: oiled / E: sealed / F: untreated / G: maintenance care product / P: polishing / S: structured / V: heavily soiled

important:

before protective treatment: the floor must be perfectly stripped, thoroughly rinsed and completely dry! **floor has to be grinded it change le system from the cired to oiled system** green and black pad on hard wood only Let dry protection treatment completely between the layers and before use Process treatement of protection: see descriptione of method

no.52 Wood parquet (oiled)



Information about the flooring



Wetrok AG cannot accept any liability for damages due to improper use.
For security information, see the safety data sheet at www.wetrok.ch.
Wear protection: gloves, safety goggles, work clothes
Follow the information and remarks on the label, product data sheet and material safety data sheet.
The product data sheet describes the product and gives information about its application, storage. See www.wetrok.ch
The recommended colours of pad and brushes consist to the actual wWetrok product range
Follow the special cleaning and care instructions of the floor manufacturer
The cleaning and care instructions are recommendations and suggestions and apply to floorings in object quality.

Strong alkalines can destroy or discolour wood coverings. Use a special basic linoleum cleaner! Wood coverings are sensitive to abrasive pads and brushes.

Permanent exposure to moisture should be avoided with wood coverings. Mop as little as possible and wring out the mop thoroughly. Allow it to dry completely before applying a protective treatment! Allow longer drying times than for non-porous coverings such as PVC. Wear a protective mask when there are fine particles of wood dust in the air, for example when sanding or dry vacuuming.



Hardwoods (deciduous wood) such as oak, beech, ash, maple, walnut and acacia, or exotic woods, are processed into parquet. Softwoods (coniferous wood) such as spruce, fir and pine are mostly used in the manufacturing of floor boards (long tongue-and-groove boards). Humidity variations cause wood to shrink (dry out) or swell (exposure to moisture) and, possibly, warp (moisture).

Distinguishing feature: appearance of wood, dull sound when tapped.



Remove loose dirt before every cleaning, damp mop smooth floors and vacuum structured floors. Cleaning agents and surface treatments may alter the appearance and properties of a floor's surface. Test on an inconspicuous spot to find which product is suitable for your requirements. Test beforehand on an inconspicuous spot to see if the cleaning agent or surface treatment damages the floor.

Dirt-trapping zones, incl. dirt-trapping mats (Wetrok Gardamat) in the entrance, at least 7m long, greatly reduce the amount of dirt tracked into the building.

If you have any questions, please don't hesitate to contact us. For training courses, contact the Wetrok Academy, tel. +41 (0)43 255 51 43 or academy@wetrok.ch.

Wetrok AG Steinackerstrasse 62, CH-8302 Kloten, Tel +41 (0)43 255 51 51, info@wetrok.ch, www.wetrok.ch, www.wetrok.com