no.55 Cork linoleum (not sealed)



cleaning system with treatment end of construction

object address

room classification

customer representative

date

work process: select one work stage from each number

R	cleaning method	recommendations * chemical products	dosage		recommendations machine / tool	comments
1	dry vacuum cleaning			Dust roller nozzle1Neverclog filter without ring1	Twinvac /	large areas: sweeping
2	dusting damp mopping			Masslinn yellow / Floorwit ye E Multi squeegee/ Masslinn 2000/Floorwit white	Balit Varifix / Balit/	
	cleaning without maintenance care pro					
3	wet mopping direct method	Ecofloor (V Reshine	0.5 - 1% 3 - 5%	Micro-Mop Top/ S Microsol mop/ V Mop Microbrush/	Socar / Drewell	
3	scrubber drying direct method	Ecofloor (V Reshine	0.5 - 1% 3 - 5%	Microsol fibre pad/	Duomatic / Laser Mambo / Samba Sprinter / iMatic	
3	wet scrubbing and wet vacuuming	Reshine Antiwax forte	3 - 5% 2 - 5%	 Microsol fibre pad/ V ● Pad blue/ 	Monomatic I / Watertank Duovac /	heavily soiled
	cleaning with maintenance care (first	protective treatment with	same proc	duct as in maintenance cleaning)		
4	wet mopping direct method	Redur	3%	Micro-Mop Top/ S Microsol mop/ Mop Microbrush/	Socar / Drewell	
4	scrubber drying direct method	Redur	3%	Microsol fibre pad/	Duomatic / Mambo / Samba Sprinter / iMatic	
4	spray cleaning full spray	Waxspray Polish	100% 33%		Monomatic DS / Spray unit	after polishing

* basic treatment / structure: B: coated / C: waxed / D: oiled / E: sealed / F: untreated / G: maintenance care product / P: polishing / S: structured / V: heavily soiled

comments

e.g. spot removal and basic cleaning with protective treatment When spray cleaning, you should change your pad often

no.55 Cork linoleum (not sealed)



	maintenance cleaning				object	t	date		_
				a	ddress	3	custome	r	
work	process: select one work stage from e	each nu	mber	room classif	ication	1	representative)	
ß	cleaning method	frequ ency	recommendations * chemical products	dosage	*	recommendations pad / brush / mop / cloth	recommendations machine / tool	comments	
1	dusting damp mopping					Masslinn / Floorwit Synthetic fur	Balit Varifix / Balit/		
1	dry vacuum cleaning					Dust roller nozzle	Monovac / Scuba	large areas: sweeping	
2	chewing gum removal		Karpfrost Karpotek	100%				if needed	
	cleaning without maintenance								
3	wet mopping direct method		Ecofloor Reshine Alcosal	0.5 - 1% 1 - 2% 1 - 2%	v	Micro-Mop Top / Mop Variwet Mop Microbrush/	Wetbox system Socar / Drewell Variwet / B. Varifix		
3	scrubber drying direct method		Ecofloor Reshine Libero	0.5 - 1% 1 - 2% 0.5 - 3%	B F S	 Pad red/ Pad blue/ Microsol fibre pad/ 	Duomatic / Mambo / Samba Sprinter / iMatic		
3	polishing, vacuum polishing				B F C) US pad yellow /) Pad blue/) Microsol fibre pad/	Monomatic US / Suction ring Monomatic HS /	after polishing	
	cleaning with maintenance				1				
3	wet mopping direct method		Redur	1%		Micro-Mop Top / Mop Variwet Mop Microbrush/	Wetbox system Socar / Drewell Variwet / B. Varifix		
3	scrubber drying direct method		Redur	1%	B F S	Pad red/ Pad blue/ Microsol fibre pad/	Duomatic / Laser Mambo / Samba Sprinter / iMatic		
3	spray cleaning partial spray		Waxspray Polish B Polyspray	100% 33% 100%	Р	Pad red/ Pad yellow/	Monomatic DS / Spray unit	after polishing	

* basic treatment / structure: B: coated / C: waxed / D: oiled / E: sealed / F: untreated / G: maintenance care product / P: polishing / S: structured / V: heavily soiled

important:

nt: When spray cleaning, you should change your pad often

no. 55 Cork linoleum (not sealed)



	interim cleaning				objec	t	date			
				a	ddress	S	customer			
work	process: select one work stage from e	each nur	mber	room classif	icatior	ו	representative			
	cleaning method	frequ ency	recommendations * chemical products	dosage	*	recommendations pad / brush / mop / cloth	recommendations machine / tool	comments		
1	dusting damp mopping					Masslinn / Floorwit Synthetic fur	Balit Varifix / Balit/			
1	dry vacuum cleaning				V	Dust roller nozzle	Monovac / Scuba			
1	vacuum sweeping sweeping						Speedmatic Twister Turbo Sweep	large areas: sweeping	2 m	
2	chewing gum removal	,	Karpfrost Karpotek	100%				if needed		
	cleaning without maintenance									
3	wet mopping indirect method		Reshine Polex	3 - 5% 2 - 4%		Micro-Mop Top / Mop Microbrush/ Flat mop/	Wetbox system Socar / Drewell			
3	scrubber drying indirect method		Reshine Polex	3 - 5% 2 - 4%	В — V — F —	Pad red/ Pad blue/ Microsol fibre pad/	Duomatic / Laser Sprinter / iMatic Mambo / Samba			
	cleaning with maintenance									
3	spray cleaning full spray		Waxspray Polish	100% 33%	P 🦲	Pad red/ Pad yellow/	Monomatic DS / Spray unit	after polishing		

* basic treatment / structure: B: coated / C: waxed / D: oiled / E: sealed / F: untreated / G: maintenance care product / P: polishing / S: structured / V: heavily soiled

important: When spray cleaning, you should change your pad often For initial cleaning after interim cleaning, see "initial cleaning".

APA 55

no. 55 Cork linoleum (not sealed)



	basic cleaning				object	date		
work	process: select one work stage from (each nu	mber	a room classif	address	customer		
	process: select one work stage from			Toom classi		-	;	
	cleaning method	frequ ency	recommendationschemical products	dosage	 recommendations * pad / brush / mop / cloth 	recommendations machine / tool	comments	
1	dusting damp mopping				Masslinn / Floorwit Synthetic fur	Balit Varifix / Balit/		
1	dry vacuum cleaning				S Dust roller nozzle	Monovac / Scuba		
2	chewing gum removal		Karpfrost Karpotek	100%			if needed	
	cleaning without maintenance							
3	wet scrubbing and wet vacuuming		B RelinoC Antiwax forte	20 - 50% 30 - 50%	B Pad green/ Pad blue/ F Microsol fibre pad/	Monomatic I / Watertank Duovac /	heavily soiled	
3	scrubber drying indirect method		B Relino C Antiwax forte	20 - 50% 30 - 50%	B Pad green/ Pad blue/ F Microsol fibre pad/	Duomatic / Laser Mambo / Samba Sprinter / iMatic	2 m	
3	spray cleaning full spray		C Antiwax forte	30 - 50%	B Pad green/ Pad blue/ F Microsol fibre pad/	Monomatic I / Spray unit Monomatic LS /	after polishing	
4	rinsing		pure water		Pad blue/ Microsol fibre pad/	Monomatic I / Duovac / Duomatic / Laser	large areas: scrubber-dryer	рН 7

* basic treatment / structure: B: coated / C: waxed / D: oiled / E: sealed / F: untreated / G: maintenance care product / P: polishing / S: structured / V: heavily soiled

important: change pad often

> Use a coin or a key to do a scratch test, to check if all the protective coating has been removed. When white abrasion occurs, carry out a full clean to remove all the protective coating

no.55 Cork linoleum (not sealed)



	protective treatment			objec	t	date	
			a	ddress	S	customer	
work	process: select one work stage from each nur	nber	room classif	icatior	ו	representative	
R	cleaning method	recommendations* chemical products	dosage	*	recommendations pad / brush / mop / cloth	recommendations machine / tool	comments
1	dusting damp mopping				Masslinn 2000/Floorwit white Synthetic fur	Balit Varifix / Balit/	
1	dry vacuum cleaning			V S	Dust roller nozzle Dust roller nozzle	Monovac / Scuba	
	pore filling (only if necessary)						
2	pore filling	F Porosol	100%		Cover for Florfix Flat mop/	Florfix / Drewell/ Buket plast 22l	If necessary, one layer on porous surface
	coating						
3	coating	Mepol HM Mepol H Stoner	100% 100% 100%		Cover for Florfix Flat mop/	Florfix / Drewell/ Buket plast 22l	1 - 3 thin layers
3	waxing	Polish	100%		Cover for Florfix Flat mop/	Florfix / Drewell/ Buket plast 22l	1 - 3 thin layers
4	dusting damp mopping				Masslinn 2000/Floorwit white Synthetic fur	Balit Varifix / Balit/	if needed
	buffing wax treatment (only if necessa	ry)					
6	polishing, vacuum polishing			c 🤇		Monomatic HS / Suction ring Monomatic DS /	after polishing

* basic treatment / structure: B: coated / C: waxed / D: oiled / E: sealed / F: untreated / G: maintenance care product / P: polishing / S: structured / V: heavily soiled

important:

before protective treatment: the floor must be perfectly stripped, thoroughly rinsed and completely dry!
 Let dry protection treatment completely between the layers and before use
 Process treatement of protection: see descriptione of method
 For initial cleaning with maintenance cleaner after protective treatment, see "initial cleaning".

no.55 Cork linoleum (not sealed)



Information about the flooring



Wetrok AG cannot accept any liability for damages due to improper use.
For security information, see the safety data sheet at www.wetrok.ch.
Wear protection: gloves, safety goggles, work clothes
Follow the information and remarks on the label, product data sheet and material safety data sheet.
The product data sheet describes the product and gives information about its application, storage. See www.wetrok.ch
The recommended colours of pad and brushes consist to the actual wWetrok product range
Follow the special cleaning and care instructions of the floor manufacturer
The cleaning and care instructions are recommendations and suggestions and apply to floorings in object quality.

Strong alkalines can destroy or discolour cork linoleum coverings. Use a special basic linoleum cleaner! Cork linoleum coverings are sensitive to abrasive pads and brushes.

Cork linoleum coverings are largely insensitive to acids, fats, oils and solvents.

Certain manufacturers give cork linoleum coverings a surface finish at the factory (first maintenance).



Cork linoleum is a 100% natural product consisting of linseed oil, wood and cork granulates, resins, colorants and limestone on a jute underlay.

Distinguishing feature: fire assay with a glowing hot needle in an inconspicuous place: needle penetrates, typical smell, crater can be removed with the fingers.



Remove loose dirt before every cleaning, damp mop smooth floors and vacuum structured floors. Cleaning agents and surface treatments may alter the appearance and properties of a floor's surface. Test on an inconspicuous spot to find which product is suitable for your requirements. Test beforehand on an inconspicuous spot to see if the cleaning agent or surface treatment damages the floor. Dirt-trapping zones, incl. dirt-trapping mats (Wetrok Gardamat) in the entrance, at least 7m long, greatly reduce the amount of dirt tracked into the building.

If you have any questions, please don't hesitate to contact us. For training courses, contact the Wetrok Academy, tel. +41 (0)43 255 51 43 or academy@wetrok.ch.

Wetrok AG Steinackerstrasse 62, CH-8302 Kloten, Tel +41 (0)43 255 51 51, info@wetrok.ch, www.wetrok.ch, www.wetrok.com