

# General instructions for cleaning and care

## no.85 Stain removal (description of method)












### Stain removal dabbing method

object \_\_\_\_\_  
address \_\_\_\_\_  
room classification \_\_\_\_\_

date \_\_\_\_\_  
customer \_\_\_\_\_  
representative \_\_\_\_\_

work process: select one work stage from each number

↓	cleaning method		frequency	recommendations chemical products	dosage	* recommendations pad / brush / mop / cloth	recommendations machine / tool	comments
1		brush vacuum cleaning	<input type="checkbox"/>			V S S	<b>Karpawel</b> Monovac / Picojet	for durable flooring only
1		dry vacuum cleaning	<input type="checkbox"/>			S <b>Dust roller nozzle</b> Combi-nozzle	<b>Monovac</b> Portavac Twinvac	
cleaning without maintenance								
2		chewing gum removal	<input type="checkbox"/>	<b>Karpfrost</b> Karpotek	<b>100%</b> 100%		<b>Monovac</b> Portavac Twinvac	repeat until clean 
3		dabbing method	<input type="checkbox"/>	<b>Karpspray</b> Karpotek	<b>100%</b> 100%	<b>Microwit SOFT</b> Microwit FINE		repeat until clean
4		dabbing method	<input type="checkbox"/>	<b>Karpfom</b> Karpotek	<b>100%</b> 100%	<b>Microwit SOFT</b> Microwit FINE		repeat until clean 
first protective treatment (with the same product as in maintenance cleaning)								
5		dabbing method	<input type="checkbox"/>	<b>Libero</b>	<b>20%</b>	<b>Microwit SOFT</b> Microwit FINE		carpet should be pretreated with Libero. 

\* basic treatment / structure: B: coated / C: waxed / D: oiled / E: sealed / F: untreated / G: maintenance care product / H: Disinfection / P: polishing / S: structured / V: heavily soiled

# General instructions for cleaning and care

## no.85 Stain removal (description of method)

















### Stain removal rinsing method

object \_\_\_\_\_  
address \_\_\_\_\_  
room classification \_\_\_\_\_

date \_\_\_\_\_  
customer \_\_\_\_\_  
representative \_\_\_\_\_

work process: select one work stage from each number

cleaning method		frequency	* recommendations chemical products	dosage	* recommendations pad / brush / mop / cloth	recommendations machine / tool	comments
1	 brush vacuum cleaning	<input type="checkbox"/>			V S S	<b>Karpawel</b> Monovac / Picojet	for durable flooring only
1	 dry vacuum cleaning	<input type="checkbox"/>			S <b>Dust roller nozzle</b> Combi-nozzle	<b>Monovac</b> Portavac Twinvac	
cleaning without maintenance							
2	 chewing gum removal	<input type="checkbox"/>	<b>Karpfrost</b> Karpotek	<b>100%</b> 100%		<b>Monovac</b> Portavac Twinvac	repeat until clean 
3	 dabbing method	<input type="checkbox"/>	<b>Karpspray</b> Karpotek	<b>100%</b> 100%	<b>Microwit SOFT</b> Microwit FINE		if needed 
4	 Wasserring	<input type="checkbox"/>		<b>0</b> <b>100%</b>			
5	 spraying	<input type="checkbox"/>	<b>Retex</b> Karpex Libero	<b>3 - 10%</b> 3 - 10% 20%		<b>SmartSpray 5</b>	Work on stain with soft brush and do not rub! 
6	 rinsing	<input type="checkbox"/>		<b>0</b> <b>100%</b>		<b>Twinvac</b>	repeat until clean
cleaning with maintenance							
3	 dabbing method	<input type="checkbox"/>	<b>Karpspray</b> Karpotek	<b>100%</b> 100%	<b>Microwit SOFT</b> Microwit FINE		if needed 
4	 rinsing	<input type="checkbox"/>	<b>Libero</b>	<b>20%</b>		<b>Twinvac</b>	carpet should be pretreated with Libero. 

\* basic treatment / structure: B: coated / C: waxed / D: oiled / E: sealed / F: untreated / G: maintenance care product / H: Disinfection / P: polishing / S: structured / V: heavily soiled

## General instructions for cleaning and care

### no. 85 Stain removal (description of method)



#### Information about the flooring



Wetrot AG cannot accept any liability for damages due to improper use.  
For security information, see the safety data sheet at [www.wetrot.com](http://www.wetrot.com).  
Wear protection: gloves, safety goggles, work clothes.  
Follow the information and remarks on the label, product data sheet and material safety data sheet.  
The product data sheet describes the product and gives information about its application, storage. See [www.wetrot.com](http://www.wetrot.com).  
The recommended colours of pad and brushes consist to the actual wWetrot product range.  
Follow the special cleaning and care instructions of the floor manufacturer.  
The cleaning and care instructions are recommendations and suggestions and apply to floorings in object quality.

---

**Textile floor coverings made from natural fibres or blended yarn (natural and synthetic fibres) require very careful cleaning. Minimal use of mechanical devices!**

**Natural fibres such as linen, jute, coconut matting, silk, sisal and wool are mostly insensitive to water.**

**Acetate, jute, camel hair, silk and wool, among others, are alkaline sensitive.**

**Acetate, wool, polyamide, among others, are acid sensitive.**

**Acetate (acetone) and polyacrylic, among others, are solvent sensitive.**

Remove stains as quickly as possible. Fresh stains are easier to remove than old ones.

Before wet cleaning, check whether the underside, the backing material and the base material are insensitive to water.

Take care when wet cleaning raised floors and use very little cleaning solution.

Turn off in-floor heating 24 hours before wet cleaning.

Depending on the manufacturing process and the surface, a distinction is made between loop fabric (Reps, Berber, bouclé), cut pile (velour) and needle felt.

The materials used (pile fabric, base material, backing material) determine the system used to clean textile floor coverings.

Distinguishing feature: fire assay: scrape off and set fire to a little fibrous material: wool smells like burnt hair and synthetic fibres melt.



Vacuum textile floors before each cleaning.

Cleaning agents and surface treatments may alter the appearance and properties of a floor's surface.

Test on an inconspicuous spot to find which product is suitable for your requirements.

Test beforehand on an inconspicuous spot to see if the cleaning agent or surface treatment damages the floor.

Dirt-trapping zones, incl. dirt-trapping mats (Wetrot Gardamat) in the entrance, at least 7m long, greatly reduce the amount of dirt tracked into the building.

If you have any questions, please don't hesitate to contact us.

For training courses, contact the Wetrot Academy, tel. +41 (0)43 255 51 43 or [academy@wetrot.ch](mailto:academy@wetrot.ch).