

### **INDUSTRIAL VACUUM CLEANERS**





# SILOVAC 100 - Single - phase industrial vacuum cleaner with direct discharge in Big Bag - Large capacity - INDUSTRIAL THREE PHASE







- √ Vacuum Silos designed to suction large quantities of material and discharge directly into big-bag or collection barrels.
- ✓ Containment capacity 100 liters.
- ✓ Material discharge by tilting flap, butterfly valve, guillotine system.
- ✓ Quick and simple big-bag bagging system.
- Wide surface filters for fine dust with manual filter shaker.
- ✓ Mounted on wheels or fixed to the floor.
- ✓ With forklift intakes for easy transport.

| SUCTION UNIT              |        |          |
|---------------------------|--------|----------|
| Voltage                   | V - Hz | 230 - 50 |
| Power                     | kW     | 3 x 1,1  |
| Max waterlift             | mmH2O  | 2.400    |
| Max air flow              | m³/h   | 540      |
| Suction inlet             | mm     | 80       |
| Butterfly discharge valve | mm     | 150      |
| Hopper                    | mm     |          |

| FILTER UNIT           |                |               |  |
|-----------------------|----------------|---------------|--|
| Filter Type           |                | Star          |  |
| Surface - Diameter    | cm²-mm         | 20.000 - 460  |  |
| Material - Efficiency | IEC 60335-2-69 | Polyester - L |  |
| Air load on filter    | m³/m²/h        | 270           |  |
| Cleaning system       |                | Manual        |  |

| COLLECTION UNIT  |     |                  |
|------------------|-----|------------------|
| Discharge system |     | Longopac bag     |
| Capacity         | lt. | 100              |
| VOLUME           |     |                  |
| Dimensions       | cm  | 136 x 145 x 291h |





# **SUCTION UNIT**

Suction is developed by three carbon brushes by-pass motors which are activated by independant switches placed on a solid, metallic head. Special noise buffers reduce noise level to work safety standards.



### FILTER UNIT

The filter is cleaned mechanically by means of a manual filter shaking lever which shakes the filter vertically, ensuring safe and effective cleaning. This contributes to maintain high suction efficiency and avoids the spreading of dust in the environment.



# **COLLECTION UNIT**

The material is discharged directly into big-bags.