

INDUSTRIAL VACUUM CLEANERS

W 3 HV - Single phase industrial vacuum cleaner 3 stage - INDUSTRIAL SINGLE PHASE



CLEANING CONTRACTORS



WOOD



SAND BLASTING



✓ 100% steel construction.

✓ Suitable for wet and dry service, also simultaneously.

✓ Detachable container with direct bagging option.

✓ Filter with wide filtration surface for fine dusts, with integrated manual cleaning system.



SUCTION UNIT

Voltage	V - Hz	230 - 50
Power	kW	3 x 1,3
Max waterlift	mmH2O	3.600
Max air flow	m ³ /h	450
Suction inlet	mm	80



FILTER UNIT

Filter Type	Star	
Surface - Diameter	cm ² -mm	20.000
Material - Efficiency	IEC 60335-2-69	Polyester - L
Cleaning system	Manual	



COLLECTION UNIT

Collection tank	Steel	
Discharge system	Roll-out container	
Capacity	lt.	65 / 100



VOLUME

Dimensions	cm	58 x 60 x 145h
------------	----	----------------



SUCTION UNIT

Suction is developed by three carbon brushes by-pass motors which are activated by independent switches placed on a solid, metallic head. Special noise buffers reduce noise level to work safety standards.



FILTER UNIT

A polyester pocket filter inside the steel filter chamber protects the suction system. A filter shaking lever allows easy cleaning for longer lasting filter life.



COLLECTION UNIT

The steel container has an easily detachable container for quick disposal of suctioned material.



OPTIONALS

- ✓ Nomex heat resistant filter up to 250°
- ✓ Absolute Hepa filter H14
- ✓ Class M filter
- ✓ PTFE coated class M filter
- ✓ Class M teflon hydro-oleophobic filter
- ✓ Antistatic class M filter
- ✓ Stainless steel collection tank and filter chamber
- ✓ Earth grounding
- ✓ Sieve grid with discharge valve and level detector
- ✓ Longopac 20m bag container
- ✓ Cyclon for filter protection